



location:
DAMP
interior

SPECIFICATIONS:

DESCRIPTION

Ultra low profile ceiling luminaire, featuring handcrafted glass. Two sizes available.

LAMPING

Standard: 40W low-pressure G9 Halogen 120V lamps, *lamp included*.
CFL: T5 Circline, 120V, *not included*.

DIFFUSER

Handcrafted glass diffuser in Opal Glossy decor.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.
90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations. Interior Use Only.




Renfro 16



Renfro 20

ORDERING:

Renfro 16:



R E N F R O 1 6 - | | | |


Fixture

Lamp Options

RENFR016 15.75" Opal Glossy

HAL 2x 40W G9
122T5 1x 22W T5 Circline, 120V

Renfro 20:




R E N F R O 2 0 - | | | |

Fixture

Lamp Options

RENFR020 19.75" Opal Glossy

HAL 3x 40W G9
140T5 1x 40W T5 Circline, 120V/277V



Edge detail

Project Information:

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 6/13