

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Name: Hartco Wood Filler
Description: Acrylic Filler

II. DEPARTMENT OF TRANSPORTATION INFORMATION

Shipping name: Not Classified Hazard Class: N/A
ID #: N/A Packing Inst.: N/A DOT/IMO/IATA: N/A
EMERGENCY ONLY CONTACT: CHEM-TEL 800-255-3924

III. HMIS (0=minimal hazard; 4 = severe hazard)

Health = 1 Flammability = 0 Reactivity = 0

IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does NOT contain asbestos.

V. PRODUCT INGREDIENTS

<u>(Chemical Identity; Common Name)</u>	<u>C.A.S. No.</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Calcium Carbonate	1317-65-3	60 – 70%	15 mg/m3 As respirable dust: 5 mg/m3	10 mg/m3
Polyvinyl Acetate	9003-20-7	8 – 10	N/A	N/A
Propylene Glycol	57-55-6	2 – 4	N/A	N/A

VI. PHYSICAL DATA

APPEARANCE AND COLOR: Tan - brown solid. ODOR: Similar to fill dirt. BOILING POINT (degrees F): N/A VAPOR PRESSURE: N/A. VAPOR DENSITY: Heavier than air. SOLUBILITY IN WATER: Insoluble. SPECIFIC GRAVITY: 1.7 PERCENT VOLATILE BY WEIGHT: 2.7%. EVAPORATION RATE: Slower than butyl acetate. PH: N/A.

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A. FLAMMABLE LIMITS IN AIR, 5 BY VOLUME: LEL = N/A; UEL = N/A. EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water spray. SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers in a fire may rupture due to pressure build-up; use water to cool containers to prevent this.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Direct dermal contact. EYE CONTACT: Contact with eyes will cause irritation. Immediately flush eyes with plenty of water for at least 15 minutes. Refer to physician if irritation develops or symptoms persist. SKIN CONTACT: Mild irritant, repeated contact may cause irritation. Remove contaminated clothing. Wash skin with soap and water. Refer to physician if irritation develops or symptoms persist. INHALATION: N/A. INGESTION: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. CARCINOGENICITY: NTP: No. IARC Monographs: No. OSHA Regulated: No. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: Existing skin conditions.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: Strong oxidizing agents. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other toxic vapors and gases that are common to thermal degradation of organic compounds. HAZARDOUS POLYMERIZATION: Will not occur.

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill, preventing it from entering sewer lines or waterways. Use absorbent to assist with the pick-up of material. Scrape up product and place into container. WASTE DISPOSAL METHOD: Do not reuse container. Dispose of container and any unused contents in accordance with Federal, State and Local Waste Disposal Regulations. Do not flush unused contents or residue down drains.

XI. SPECIAL HANDLING AND USE INFORMATION

VENTILATION: Normal ambient ventilation should be sufficient. RESPIRATORY PROTECTION: Should not be required. SKIN AND EYE PROTECTION: It is always a good safety practice to avoid contact with eyes and prolonged contact with skin. If contact may occur, use spectacle-type glasses and latex or rubber gloves.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep from freezing. Recommended storage temperature is below 90°F. OTHER PRECAUTIONS: None. WORK SITE ENVIRONMENT: Initially there may be a potential adverse impact on indoor air quality within the general work area during the installation process. Therefore you should advise the building manager or other appropriate person that: It will be necessary to establish and maintain adequate ventilation of the work area, without causing the entry of contaminants to other parts of the building. Persons who are sensitive to odors and/or chemicals should be advised to avoid the work area during this process.

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

N/A - not applicable or not available N/K - none known or not known

Hartco[®]
Quality Wood Flooring

from **Armstrong**

Wood Filler

Prepared 6/09

Armstrong World Industries, Inc.
P. O. Box 3001
Lancaster, PA 17604
1-877-276-7876, Option 2,3,3

