# **FACT SHEET**

# SURETREAD™ & PAVERS™

# with QUARRY GUARD™ & MICROBAN®

# **QUARRY**



- Improves the grout release and stain resistance of the tile, resulting in easier clean-up with installation and tile that is less likely to get stained in the future.
- MICROBAN ANTIMICROBIAL PROTECTION
  - Microban® antimicrobial technology is infused into Daltile Quarry Guard™ during the manufacturing process to inhibit the growth of stain-causing bacteria on the Quarry Guard
  - On an unprotected surface, bacteria can double in number every 20 minutes. Microban® protection works continuously to keep the Quarry Guard™ cleaner, longer.
- SUPERB TILE PERFORMANCE
- Durable, stain resistant surface.
- Easier clean-up after installation.
- Perfect for high-traffic areas.
- UPDATED COLOR PALETTE
  - Expanded color palette provides larger selection.
  - Available in smooth or textured surface.

Performance, durability, and selection, all in a Quarry Tile.

## **COLORS**

### PAVER SURFACE



RED 0Q84 (1)



CHOCOLATE 0Q89 (2)



WHEAT 0O80 (2)



BLACK 0Q74 (2)



GOLDEN BROWN 0078 (2)



BRONZE CLAY



GRAY 0O85 (2)



STORM GRAY 0083 (2)

## SURETREAD SURFACE



RED 0Q81 (1)



CHOCOLATE 0Q88 (2)



WHEAT 0079 (2)



BLACK 0Q73 (2)



GOLDEN BROWN 0Q75 (2)



BRONZE CLAY 0Q86 (2)



GRAY 0Q76 (2)



STORM GRAY 0Q82 (2)

**SIZES** 

6 x 6 Field Tile

TRIM (Smooth Surface only)

6 x 6 Bullnose

(1) & (2) indicate price groups, (1) being the least expensive.

6 x 6 Bullnose Corner 6 x 6 Cove Base

6 x 6 Cove Base Corner Right 6 x 6 Cove Base Corner Left 3/4 x 6 Cove Inside Corner







Microban® Antimicrobial Technology is not designed to replace normal cleaning practices or protect users against food-borne illness. MICROBAN is a registered trademark of Microban Products Company.

# **FACT SHEET**



# SURETREAD & PAVERS QUARRY

with QUARRY GUARD™ & MICROBAN®

# **APPLICATIONS**

APPLICATION	INTERIOR			EXTERIOR	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors/Patios	✓	<b>✓</b>	✓		
Walls/Backsplashes	✓	<b>✓</b>	✓	<b>✓</b>	✓
Countertops	✓	<b>✓</b>	✓	<b>✓</b>	✓
Pool Decking					
Pool Lining	✓	<b>✓</b>	<b>✓</b>	~	<b>✓</b>

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed. Suitable for industrial applications requiring high compressive strength.

## **TEST RESULTS**

	ASTM#	Result
Water Absorption	C373	< 3.0%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	7
Chemical Resistance	C650	Resistant
Coefficient of Friction	C1028	Wet: ≥ 0.60 Dry: ≥ 0.60
Dynamic Coefficient of Friction*	D.C.O.F.	Wet: ≥ 0.42

<sup>\*</sup>Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTestTM helps to assess a products suitability for a commercial environment.

## INSTALLATION

Thickness	Grout Joint Recommendation	Shade Variation	
3/8''	3/8''	Medium (V2)	

## MANUFACTURING LOCATION

USA





Microban® Antimicrobial Technology is not designed to replace normal cleaning practices or protect users against food-borne illness. MICROBAN is a registered trademark of Microban Products Company.