

BAY BRIDGE™

COLORBODY™ PORCELAIN



Connecting Contemporary Style with Ultimate Durability.

If you're looking for a contemporary tile that offers unique visual appeal and top notch durability, Bay Bridge™ is the perfect selection. Bridging the gap between modern and rustic style, Bay Bridge™, fuses the beauty of natural wood with the modernity of fabric and concrete to create a unique and contemporary new look. Its durable designs mimic the natural and irregular patterns of wood grain, fabric weaves and stained concrete. Specifically intended for high-traffic areas, as opposed to natural wood, cloth, and even concrete, this style withstands high-moisture too. Finished with a reflective glaze, these fresh interpretations come in variety of contemporary colors to complement your space.



Field Tile



VISTA BB10



ASHWOOD BB11



TRESTLE BB12



MAINLAND BB13

CREATIVE IDEAS

VISTA



ASHWOOD



TRESTLE



MAINLAND



FASHION ACCENTS™ GOLD SWIRL F003 2 x I2 Convex Accent



MARTINIQUE LIMESTONE ARCTIC GRAY L757 2 x 6 Split Face Mosaic



CORTONA™ WHITE FLORA CR14 4 x 13 Decorative Accent



FASHION ACCENTS™ NICKEL BLEND FA64 Brix Mosaic

Backsplash Design Ideas



Backsplash features I \times 6 Antique Nickel IM02 Accent Liner, 6 \times 24 Mainland BBI3 and Nickel Blend FA64 Brix Mosaic.

Pattern Ideas



BRICKWORK



LINEAR STACK



STAGGERED BRICKWORK VERTICAL



HERRINGBONE



BAY BRIDGE™ colorbody™ porcelain

SIZES

		SQ.FT. CARTON	PCS. PER CARTON
24 x 24 Field Tile	(23-7/16" x 23-7/16") (59.44 cm x 59.44 cm)	15.42	4
I2 x 24 Field Tile	(11-5/8" x 23-7/16") (29.56 cm x 59.44 cm)	15.38	8
I2 x I2 Field Tile	(11-5/8" x 11-5/8") (29.56 cm x 29.56 cm)	10.55	П
6 x 24 Field Tile	(5-3/4" x 23-7/16") (14.63 cm x 59.44 cm)	10.65	П

RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	\bigvee	С	EP	

COMMERCIAL USAGE

		INTERIOR		EXTE	RIOR
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios	✓	✓	✓	~	✓
Walls/Backsplashes	~	✓	~	~	~
Countertops	~	✓	~	~	~
Pool Decking					
Pool Linings	~	✓	~	✓	✓

Suitable for exterior patios (excluding pool decks) and walls in freezing and non-freezing climates when proper installation methods are followed.

Cove base and outcorners are clay body ceramic and recommended for exterior application in non-freezing climates only.

NOTES

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Special care needs to be given when installing tiles 20" and larger. Please refer to $www. daltile products. com/Large Tiles \ for \ information.$

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information, refer to "Factors to Consider" at www.daltile.com/ CommercialFactors.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

TRIM

TYPE	NUMBER	SIZE	PCS. PER CARTON
Floor Bullnose ▲*	S-43C9	3 x 12	30
Cove Base *	S-36C9T	6 x 12	22
Cove Outcorner *	SC-36C9T	I×6	15

[▲]Graphic runs vertically

SHADE VARIATION



RANDOM (V4)

Extreme color and texture variation from tile to tile and within each tile; a random look.

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION	
3/8" Field Tile	1/8" (3/16" when rectangular sizes are used	
5/16" Cove Base & Outcorner	in a staggered brick-joint pattern, where the overlap does not exceed 33%)	

DYNAMIC C.O.F. (WET): 2
The higher the rating, the higher the slip resistance.

I < 0.42 2 ≥ 0.42

STATIC C.O.F. (WET): 2

1 0.50 - 0.59 2 ≥ 0.60

TEST RESULTS

ASTM#	RESULT
C373	< 0.5%
C648	> 275 lbs
MOHS	8.0
C650	Resistant
A137.1	Wet: ≥ 0.42
C1028	Wet: ≥ 0.60 Dry: ≥ 0.70
C1027	N/A
	C373 C648 MOHS C650 A137.1 C1028

Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTestSM helps to assess a product's suitability for a commercial environment. For more information, visit our website at www.daltile.com/DCOF.

^{*}Cove Base and Floor Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

BAY BRIDGE™

COLORBODY™ PORCELAIN



floor ullet wall ullet countertop





By their very design, Daltile products can help make it easier for you to earn LEED[™] points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.











