

GENERAL

Highest quality sink formed of #18 (1.2mm) gauge, type 304 (18-8) nickel bearing stainless steel. Undermount.

DESIGN FEATURES

Bowl Depth: 7-7/8" (200mm).

Coved Corners: 1-3/4" (44mm) vertical and horizontal radius. Finish: Exposed surfaces are hand blended to a lustrous satin finish

Underside: Underside of sink is fully protected by heavy duty Sound Guard® undercoating to prevent condensation and dampen sound.

OTHER

Drain Opening: 3-1/2" (89mm).

Note: All Elkay undermount sinks are designed to affix to the

underside of any solid surface countertop. Installation: See illustrated profile below. These sinks comply with ASME A112.19.3.


OPTIONAL ACCESSORIES

Cutting Boards (for ELUH model only): CBR1418, CBS1418.

Drain: LK99.


Rinsing Basket: LKWRB1418SS.


Utensil Caddy for Rinsing Basket: LKWUCSS.



Installation Profile of ELU and ELUH Models

The template provided with each ELU/ELUH sink provides the only type of installation recommended by Elkay.





SEE OTHER SIDE FOR PRODUCT DIMENSIONS.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkayusa.com for most current version of Elkay product specification sheets.


This specification describes an Elkay product with design, quality and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

1 - 317




SINK DIMENSIONS*

Model	Overall		Inside Bowl			Cutout in	Minimum Cabinet
Number	L	W	L	W	D	Countertop	Size
ELU1814	19 ¹ / ₂ (495mm)	15 ¹ / ₂ (394mm)	18 (457mm)	14 (356mm)	7 ⁷ / ₈ (200mm)	Template**	24 (610mm)
ELUH1814	20 ¹ / ₂ (521mm)	16 ¹ / ₂ (419mm)	18 (457mm)	14 (356mm)	7 ⁷ / ₈ (200mm)		24 (610mm)



ELU1814 Illustrated



ELUH1814 Illustrated

^{*}Length is left to right. Width is front to back. **Template and countertop mounting clips are packed with every sink.