

## Cast Bronze Keyed Plates, Double Cylinder

#5 (7071/7671), Rectangular Style (7361/7561), #16 Style (6021/6621)

- Standard Door Thickness: 1<sup>1</sup>/2"- 2" Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2<sup>1</sup>/2" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 2"- 2<sup>1</sup>/2" **Extended Components:**
- Long Double Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- · Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- · 3" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- · Deadbolt Strike Plate

- Extended Door Thickness:  $2^{1/4}$ "-  $2^{3/4}$ " Extended Components:
- Long Double Cylinder Tailpiece
- · Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3 1/2" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

## Wrought Steel #5 Keyed Plates, Double Cylinder (7011)

- Standard Door Thickness: 1<sup>5</sup>/8"- 1<sup>3</sup>/4" Standard Components:
- Double Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 1<sup>3</sup>/4"- 2<sup>3</sup>/8" Extended Components:
- Long Double Cylinder Tailpiece
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3<sup>1</sup>/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

## Wrought Steel Non-Keyed Plate (passage/privacy) (7105/7205)

- Standard Door Thickness: 1<sup>1</sup>/<sub>4</sub>"- 1<sup>3</sup>/<sub>4</sub>"
  Standard Components:
- Privacy Pin (for privacy sets)
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- Full-Lip Strike Plate

- Extended Door Thickness: 1<sup>3</sup>/4"- 2<sup>3</sup>/8" Extended Components:
- Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- · Extended Full-Lip Strike Plate
- Extended Door Thickness: 1<sup>3</sup>/4"- 2<sup>3</sup>/8" Extended Components:
- Privacy Pin w/Extension (for privacy sets)• Privacy Pin w/Extension (for privacy sets)
  - · Long Inside Passage Half Spindle
  - 1" Wood Screws
  - Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
  - · Extended Full-Lip Strike Plate

## Wrought Steel #5 Style Keyed Plates, Single Cylinder (7010)

- Standard Door Thickness: 1<sup>1</sup>/2"- 1<sup>3</sup>/4"
  Standard Components:
- Single Cylinder Tailpiece
- Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2<sup>1</sup>/4" Deadbolt Mounting Screws
- Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extended Door Thickness: 1<sup>3</sup>/4"- 2<sup>1</sup>/4" Extended Door Thickness: 2<sup>1</sup>/4"- 2<sup>3</sup>/4" Extended Components:
- Long Single Cylinder Tailpiece
- Long Inside Passage Half Spindle
- 1" Wood Screws
- · Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 2<sup>1</sup>/2" Deadbolt Mounting Screws
- Extended Full-Lip Strike Plate
- Deadbolt Strike Plate

- Extra Long Single Cylinder Tailpiece
- Extra Long Inside Passage Half Spindle
- 1" Wood Screws
- Threaded Tubes & Machine Screws supplied upon request for Hollow-Core Doors
- 3" Deadbolt Mounting Screws
- · Extended Full-Lip Strike Plate
- Deadbolt Strike Plate