



Product Specifications for E22476-75PC

|           |           |
|-----------|-----------|
| Job Name: | Job Type: |
| Quantity: | Comments: |



**E22476-75PC**  
**FunL 3-Light LED Pendant**

**Finish**  
Polished Chrome

**Glass/Shade**  
Clear Acrylic

**Product Category**

**Lamping**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| <b>Number of Bulb(s)</b>          | 3                                |
| <b>Light Type</b>                 | LED                              |
| <b>Bulb Type</b>                  | LED                              |
| <b>Max Bulb Wattage</b>           | 3                                |
| <b>Max Fixture Wattage</b>        | 9                                |
| <b>Rated Life</b>                 | ±40,000 Hours                    |
| <b>Rated Lumens</b>               | ±720                             |
| <b>Color Temp</b>                 | ±3,000 K                         |
| <b>Bulb(s) Included</b>           | Yes                              |
| <b>Light Up/Down</b>              | N/A                              |
| <b>Beam Spread</b>                | N/A                              |
| <b>CRI</b>                        | N/A                              |
| <b>Photo Cell Included</b>        | N/A                              |
| <b>Ballast/Driver/Transformer</b> | No                               |
| <b>Dimmable</b>                   | Low-Voltage<br>Electronic Dimmer |

**Measurements**

|                           |             |
|---------------------------|-------------|
| <b>Width</b>              | 21.50"      |
| <b>Height</b>             | 8.50"       |
| <b>Length</b>             | N/A         |
| <b>Extension</b>          | N/A         |
| <b>Back Plate Width</b>   | N/A         |
| <b>Back Plate Height</b>  | N/A         |
| <b>HCO</b>                | N/A         |
| <b>Min Overall Height</b> | N/A         |
| <b>Max Overall Height</b> | 129.75"     |
| <b>Hanging Weight</b>     | 10.96 lb(s) |
| <b>Height Adjustable</b>  | Yes         |
| <b>Slope</b>              | N/A         |
| <b>Chain Length</b>       | N/A         |
| <b>Wire Length</b>        | N/A         |
| <b>Canopy Width</b>       | 4.8"        |
| <b>Canopy Height</b>      |             |
| <b>Canopy Length</b>      | N/A         |

**Shipping**

|                           |             |
|---------------------------|-------------|
| <b>Carton Weight</b>      | 16.50 lb(s) |
| <b>Carton Width</b>       | 9.80"       |
| <b>Carton Height</b>      | 11.00"      |
| <b>Carton Length</b>      | 26.00"      |
| <b>Carton Cubic Feet</b>  | N/A         |
| <b>Master Pack</b>        | 1           |
| <b>Master Pack Weight</b> | N/A         |
| <b>Master Pack Width</b>  | N/A         |
| <b>Master Pack Height</b> | N/A         |
| <b>Master Pack Length</b> | N/A         |
| <b>Master Cubic Feet</b>  | N/A         |
| <b>UPS Shippable</b>      | Yes         |

**Certification**

|                      |     |
|----------------------|-----|
| <b>Safety Rating</b> | DRY |
| <b>Energy Star</b>   | No  |
| <b>CA Title 24</b>   | No  |
| <b>CA Title 20</b>   | No  |
| <b>ADA</b>           | No  |

**Other**

|                 |              |
|-----------------|--------------|
| <b>UPC Code</b> | 845094061229 |
| <b>Material</b> | Metal        |

**Equivalents**

|                           |     |
|---------------------------|-----|
| <b>Incandescent Watts</b> | N/A |
| <b>Fluorescent Watts</b>  | N/A |

ET2 Contemporary Lighting and all designs, logos and images © 2014 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.