

Electronic dishwashers'

		BUILT-IN			
		FULLY-INTEGRATED			
		LFA-086 XL LFA-086 XL IT	LFA-073 IT LFA-073 SS	LFA-65 IT LFA-65 SS	LFA-65 ITX
GENERAL FEATURES					
Electronic control		●	●	●	●
Place settings		12	12	12	12
Alternative wash		●	●	●	●
Perfect Drying		●	●		
Heat drying				●	●
ECO-Sensor		●	●		
Variable consumption		●	●	●	●
Can be connected to the hot water network		●	●	●	●
Electronic regeneration		●			
High power de-scaler		●			
Third Sprinkler		●	●		●
Third Sprayer				●	
WASH CYCLES					
Programs	Pre-wash	●	●	●	●
	Normal (150°F)	130°F		●	●
	Intensive (155°F)	●	●	●	●
	Glassware (113°F)	●			
	Delicate (130°F)	●			
	Super-intensive (161°F)		●	●	●
	Super-intensive (ETL Sanitation Listed)	●			
	Economy (150°F)	131°F	●	●	●
	Express 15 minutes (105°F)		●		
	Mixed (130°F)		●		
	Quick (130°F)	136°F	●	●	●
	Automatic (130-150°F)		●		
	Sanitizer (ETL Sanitation Listed)	●			
	Dish warming (156°F)	●			
Total number of wash programs		10	8	6	6
CONTROLS					
Buttons	Dual Zone	●	●	●	●
	Time delay	Display (9 h)	Display (19 h)	3, 6, 9 h	3, 6, 9 h
	Start-Stop control	●	●	●	●
Cycle pilot				●	●
Time remaining indicator			Display		
Rinse Aid indicator		●	●	●	●
Acoustic signal		●	●	●	●
RACKS					
Baskets gray anthracite		●	●	●	●
Effortless telescoping upper rack		●	●	●	●
Bottom rack with folding supports		●	●	●	●
SAFETY					
Hidden element		●	●	●	●
Aqua-stop		●	●	●	●
Anti-overflow		●	●	●	●
Aqua-control		●	●	●	●
Anti-water return		●	●	●	●
Anti-Heating		●	●	●	●
ENERGY CARD					
Noise pressure			33	35	35
Noise power		45	45	47	47
ELECTRICAL REQUIREMENTS					
115V, 60Hz, 13A		●			
120V, 60Hz, 15A			●	●	●
Total power (W)		1300	1360	1360	1360
Consumption/cycle: Water (gallons)		3.96	3.70	3.70	3.70
DIMENSIONS					
Height adjustment on feet (max. 2 ³ / ₄ "		●	●	●	●
Front level adjustment		●	●	●	●
Dimensions without worktop (inches)	Height	33 ⁷ / ₈ "	32 ¹ / ₄ "	32 ¹ / ₄ "	32 ¹ / ₄ "
	Width	23 ⁹ / ₁₆ "	23 ⁷ / ₁₆ "	23 ⁷ / ₁₆ "	23 ⁷ / ₁₆ "
	Depth	23 ⁵ / ₈ "	21 ¹ / ₂ " / 22"	21 ¹ / ₂ " / 22"	22"