


Top Hung System

HAWA–Junior 80/GS

Fitting Set, for a single sliding glass door without upper track and lower guide channel

1 Set				940.81.000
consisting of:	Description	Material/Color	Qty.	ltem No.
	Double roller running gear		2 pcs.	940.80.012
	Suspension bolt, M10		2 pcs.	941.00.072
	Clamp shoe, adjustable from 6 - 12.7 mm (1/4" - 1/2")	aluminum	2 pcs.	941.00.020
	Track stopper		2 pcs.	940.80.041
	Floor guide, adjustable from 6 - 12.7 mm (1/4" - 1/2")		1 pc.	941.00.031
	Buffer	rubber, black	1 pc.	407.01.930

Note: • Item numbers are valid for only 1 piece, when ordering individual components please state the desired amount
• For 2 bi-parting sliding glass doors please order 2 sets



Upper Tracks, pre-drilled Material: aluminum, anodized, clear

Length	Item No.		
1.4 m (4' 7 1/8")	940.80.140		
1.6 m (5' 3")	940.80.160		
1.8 m (5' 10 7/8")	940.80.180		
2.0 m (6' 6 3/4")	940.80.200		
2.2 m (7' 2 5/8")	940.80.220		
2.5 m (8' 2 7/16")	940.80.250		
3.0 m (9' 10 1/8")	940.80.300		
4.0 m (13' 1 1/2")	940.80.400		
6.0 m (19' 8 1/4")	940.80.600		
Packing: 1 pc			

Packing: 1 pc.

Accessories


• HAWA-Angle profile for wall mounting, (refer to pages 394-395)




- Sliding door lock HAWA-Toplock, (refer to pages 396-400)
- Lower guide channel, (refer to page 405)
- Clip-on fascias and end caps to clamp shoe, (refer to page 337)
- Floor mounted door stop, (refer to page **313**)
- Glass edge protection seals, (refer to page 405)
- Smuso AD soft-close, (refer to page 410)

Floor guide adjustment: 6 - 12.7 mm (1/4" - 1/2")

Clamp shoe adjustment: 6 - 12.7 mm (1/4" - 1/2")







The retaining force can be adjusted with a hex key.

Installation Plan: (included in fitting set), mounting instructions for planning and execution available upon request.

Dimensions in mm are exact Inches are approximate

Call 1-800-423-3531 from anywhere in the US - www.hafele.com™