

# Assembly & Installation Instructions

A318

Eddy Pendant 137570

Page 1 of 4

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## Stem Assembly (Figure 1)


### Component Parts

- A Fixture Pipe
- B Fixture Coupling

1. Carefully unpack the fixture from the carton.
2. Carefully thread fixture pipe (A), threaded end first, over fixture wires.
3. Apply a drop of the supplied thread locking compound to the internal threads of fixture coupling (B) and screw stem into fixture, being careful not to twist or pinch the wires.

**Note:** Application of the thread locking compound is necessary to prevent the stem from loosening during regular maintenance and cleaning of the fixture. Be certain to apply the compound.

4. See instructions below to complete the installation.



(Figure 1)

## Prepare the Canopy (Figure 2)


### Component Parts

- C Crossbar
- D Jam Nut
- E Threaded Nipple
- F Canopy
- G Canopy Ring

**CAUTION:** BE SURE POWER IS OFF AT THE MAIN BREAKER BOX PRIOR TO INSTALLATION.

1. Thread the jam nut (D) and crossbar (C) onto threaded nipple (E); leave both parts loose.
2. Using two machine screws (not provided), temporarily fasten the crossbar (C) to the electric box.

**Note:** A new electric box comes with screws. When replacing a fixture, retain the existing screws for use with the new fixture.



(Figure 2)

(Continued)


If you need further assistance, or find that you are missing any parts, please contact the dealer from which you purchased this product. We hope you enjoy your fixture!

\* Hubbardton Forge will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.

## Prepare the Canopy (Figure 2)

(Continued)

- Adjust the length of threaded nipple (E) in crossbar (C) so that canopy ring (G) will hold canopy (F) against the ceiling with no threads showing for best appearance. When the correct adjustment is established, tighten jam nut (D) against crossbar (C) to hold the adjustment.
- Remove the crossbar and stem from the electrical box and proceed with the assembly instructions.



(Figure 3)


## Complete Assembly & Install Fixture (Figures 3 & 4)

### Component Parts

|                   |                         |
|-------------------|-------------------------|
| A Fixture Pipe    | G Canopy Ring           |
| C Crossbar        | H Crossbar Ground Screw |
| D Jam Nut         | I Canopy Pipe           |
| E Threaded Nipple | J Plastic Sleeve        |
| F Canopy          | K Clutch                |
|                   | L Set Screw             |

**CAUTION:** BE SURE POWER IS OFF AT THE MAIN BREAKER BOX PRIOR TO INSTALLATION.

- Place canopy (F) over canopy pipe, followed by canopy ring (G). Make sure smaller diameter side of canopy ring is oriented up toward the canopy.
- Unscrew the clutch (I) from the fixture pipe; slide it across the wires and onto the canopy pipe. Follow this with the plastic clutch sleeve (H), oriented so the tapered end of the clutch sleeve nests in the clutch. (Figure 3).
- Slide the canopy pipe as far as necessary to give you the total length of the fixture which you desire. Be careful not to scratch the pipe surfaces and to pull excess wire up through the canopy pipe. There must be a minimum 1-1/2" of inner pipe inside the outer pipe. Hand-tighten the clutch to temporarily hold this adjustment. The clutch is not securely fastened at this point; do not depend on it to hold the fixture. *Important: To ensure full connection strength, be sure the tapered end of the plastic clutch sleeve (H) is oriented toward the clutch (I) when assembled and securely tighten set screw (J) (Figure 3).*



(Figure 4)

(Continued)

If you need further assistance, or find that you are missing any parts, please contact the dealer from which you purchased this product. We hope you enjoy your fixture!

\*Hubbardton Forge will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.

## Complete Assembly & Install Fixture (Figures 3 & 4)

(Continued)


- Carefully slide canopy ring (G) and canopy (F) down over fixture pipe (A) until they rest on the fixture.
- Using two machine screws (not provided), fasten the cross bar to the electric box.

**Note:** A new electric box comes with screws. When replacing a fixture, retain the existing screws for use with the new fixture.

- Using suitable wire connectors (not provided), connect fixture wires to supply wires (white to white supply, black to black supply, and bare copper to bare copper or green supply). Run a pigtail lead from crossbar ground screw (H) to the junction box and connect all ground wires (bare copper or green to bare copper or green). Push wires back into outlet box.

**CAUTION:** MAKE SURE WIRE CONNECTORS ARE TWISTED ON SECURELY, AND NO BARE WIRE IS EXPOSED.

- Slide fixture canopy (F) against ceiling, and secure with canopy ring (G).
- Once the fixture is fastened to the ceiling, tighten the set screw (L) on the clutch (K) firmly with hex wrench provided. Only after the set screw is tight should you install the glass.



(Figure 4)

(Continued)

If you need further assistance, or find that you are missing any parts, please contact the dealer from which you purchased this product. We hope you enjoy your fixture!

\* Hubbardton Forge will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.

# Assembly & Installation Instructions

A318

Eddy Pendant 137570


Page 4 of 4

## To Install Double Glass Option (Figure 5)

### Component Parts

- M Socket (6)
- N Bulb (6-included)
- O Double Glass (6)
- P Metal Tube (6)

1. Install light bulb (N). Be careful not to touch bulb with bare hands; oil from the hands will dramatically reduce bulb life.  
  
**Note:** The bulb included is based on our design preference; see the fixture wattage sticker for Max wattage information.
2. Carefully lower the metal tube (P) around the inner tube of the glass (O) until it rests on the bottom.
3. Install glass (O) by rotating it clockwise while holding the fixture assembly until it rests against the fixture. Do not over tighten.
4. Repeat steps 1-3 for remaining sockets.
5. Restore electricity at main breaker.




(Figure 5)

## To Install Short Glass Option (Figure 6)

### Component Parts

- M Socket (6)
- N Bulb (6-included)
- Q Short Glass (6)
- R Retaining Ring (6)
- S Retaining Ring Tool

1. Install light bulb (N). Be careful not to touch bulb with bare hands; oil from the hands will dramatically reduce bulb life.  
  
**Note:** The bulb included is based on our design preference; see the fixture wattage sticker for Max wattage information.
2. Slip glass (Q) over socket. Thread retaining ring (R) onto socket (M) using the provided retaining ring tool (S).
3. Repeat steps 1 & 2 for remaining sockets.
4. Restore electricity at main breaker.



(Figure 6)

If you need further assistance, or find that you are missing any parts, please contact the dealer from which you purchased this product. We hope you enjoy your fixture!

\*Hubbardton Forge will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.