



YTA19K42

Husqvarna's yard tractors offer premium performance with quality results. Their compact size makes them easy to maneuver and require less space for storage. Features such as fender-mounted cutting height adjustment, adjustable seat and an ergonomic steering wheel make these tractors simple and comfortable to operate. These tractors feature an automatic transmission for smooth, variable forward and reverse speed. Air Induction mowing technology improves airflow within the deck, ensuring a clean, consistent cut every time. For added versatility, all models can be equipped with a range of towable accessories and mulch kit for effective lawn fertilization.



KOHLER® COURAGE ENGINE
Fully pressure-lubricated, single-cylinder KOHLER® Courage engine with oil pump and oil filter. Powerful and quiet.



CRUISE CONTROL
A convenient, efficient function that ensures the tractor keeps an even speed, even if the lawn is undulating or sloping.



STEP-THROUGH
Ensures comfortable and easy mounting and dismounting.



FENDER-MOUNTED CUTTING HEIGHT ADJUSTMENT
Easy accessible cutting height adjustment for improved ergonomics. The spring-assisted cutting deck makes adjustment easier.

Features

- Adjustable seat, while seated
- Ergonomic steering wheel
- Manual blade engagement
- Cast front axle for superior stability
- Air Induction; excellent cutting performance
- Anti-scalp wheels
- Deck Wash Port
- Hour meter with service minder
- Cup holder for refreshments while mowing
- Headlights for operation in dark conditions
- Collector available as accessory

Technical data

| | |
|---------------------------------------|--|
| Engine manufacturer | Kohler |
| Engine name | Courage |
| Power | 19 hp |
| Cylinder displacement | 597 cc |
| Cylinders | 1 |
| Engine cooling | Air |
| Generator | 15 A |
| Battery | 12 V 28 Ah |
| Fuel Type | Gasoline |
| Fuel tank volume (with reserve) | 2.5 gal. |
| Fuel tank location | Front |
| Engine lubrication type | Pressure with Oilfilter |
| Oil filter | Yes |
| Transmission type | Automatic |
| Drive method | Lever-operated |
| Speed forward, min-max | 0-5.2 mph |
| Speed reverse, min-max | 0-2.9 mph |
| Cutting width | 42 inch |
| Cutting deck type | Stamped |
| Cutting deck material | Steel |
| Cutting methods | Side discharge |
| Cutting height, min-max (approximate) | 1.5 - 4 inch |
| Cutting height adjustment | Notch |
| Cutting height steps | 6 |
| Cutting height adjuster | Fender-mounted |
| Blade engagement | Manual |
| Blades | 2 |
| Blade type | Hi Performance |
| Anti-scalp wheels | 2 |
| Powder-coated cutting deck | Yes |
| Deck Wash Port | Yes |
| Seat back height | Medium |
| Seat material | Vinyl |
| Steering wheel type | Deluxe Overmolded |
| Front-End Protection | Optional |
| Hour meter | Yes |
| Collector | Available as accessory |
| BioClip® kit/plate | Available as accessory |
| Tire size, front | 15x6-6" |
| Tire size, rear | 18x9.5-8" |
| Turning radius, min | 16" |
| Wheelbase | 48" |
| Base machine, length | 69.3 inch |
| Base machine, width (chute down) | 49 inch |
| Base machine, width (chute up) | 44 inch |
| Base machine, height | 41.4 inch |
| Weight | 430 lbs |
| Homeowner Warranty | 3 Year Limited / 5 Year Chassis and Axle |

| ARTICLES | | |
|--------------|---|-------------|
| 960 43 01-39 | 19 HP 42" Tractor (Kohler) | \$ 1,499.95 |
| 960 43 01-42 | 19 HP 42" Tractor (Kohler) CARB Compliant | \$ 1,549.95 |

