

- Turn off power.
- Find the appropriate threaded holes on mounting strap. Assemble mounting screws into threaded holes.
- Attach mounting strap to outlet box. (Screws not provided)
- 4)
- Mounting strap can be adjusted to suit position of fixture.

  Grounding instructions: (See Illus. A or B).


  A) On fixtures where mounting strap is provided with a hole and two raise dimples. Wrap ground wire from outlet box around green
  - ground screw, and thread into hol\
    On fixtures where a cupped washer is provided. Put ground wire B) from outlet box under cupped washer and green ground screw

and thread screw into hole in mounting strap.

If fixture is provided with ground wire. Connect fixture ground wire to outlet box ground wire with wire connector, after following the above steps. Never connect ground wire to black or white power supply wires.

A

B



Make wire connections (connectors not provided.) Reference chart below for correct connections and wire accordingly

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor
*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)  Neutral Wire	

- Push fixture to ceiling, carefully passing mounting screws through holes. 6)
- Secure fixture to ceiling with threaded balls
- 8) Screw short end of threaded pipe with bead into bracket in center of socket cluster.
- Slip flat washer then rubber washer over end of threaded pipe.
- 10) Raise shade up to fixture.11) Slip rubber washer then flat washer over threaded pipe and screw hexnut on to end of threaded pipe.
- 12) Pass trim over threaded pipe and screw finial onto end of threaded pipe. (DO NOT over tighten.)
- 13) Slip hook at bottom of decorative chain through loop on inside of shade.

Date Issued: 11/30/07 IS-65291-US