

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	15326 AZT, AZT6, BKT - CENTER MOUNT	15011 AZT, BKT - ONE TIER																																																																																
Description	Unobtrusive, center mount fixture for maximum light spread. Coordinates with matching deck light 15065 on page 109.	Versatile fixture with wider light distribution for paths and low areas of groundcover. Louver inverts to create more indirect light spread. Mounting stems and bollard kits sold separately. Coordinates with matching deck light 15065 on page 109																																																																																
Ordering Guide & Finish	15326 AZT - Textured Architectural Bronze 15326 AZT6 - Same as 15326 AZT. Bulk packed in 6 (unbreakable master) 15326 BKT - Textured Black	15011 AZT - Textured Architectural Bronze 15011 BKT - Textured Black																																																																																
Housing	Cast Aluminum	Cast Aluminum with molded ribbed diffuser of clear UV stabilized high impact resistant polycarbonate																																																																																
Lamp Base	12V S8 wedge base socket	12V S8 wedge base socket																																																																																
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																																																																
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)	18.5-W(VA) 3155K (15599 CLR)																																																																																
LED Lamp Options	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																																																																
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connector supplied	52" of usable #18-2, SPT-1-W leads. Cable connector supplied																																																																																
Mounting Acces. Included	8" In-ground stake and 18" stem	NA																																																																																
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15656, 15657, 15658 or 15570 - Stems 15575 BK, 15576 or 15578 BK - Stakes 15665, 15666 or 15667 - Bollard 15671 ST - Bollard Template Kit 15601 - Surface Mounting Flange 15602 - Flange Mounting Nipple 15607 - Surface Mounting Bracket																																																																																
Integrated LED Option	15826 - on Page 16	NA																																																																																
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>21.8</td> <td>5.3</td> <td>1.5</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18" (as supplied)</td> <td>16.6</td> <td>6.3</td> <td>2.2</td> <td>.87</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>7.9</td> <td>6.1</td> <td>2.7</td> <td>1.2</td> <td>.55</td> <td>.2</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	21.8	5.3	1.5	.1	-	-	-	-	-	18" (as supplied)	16.6	6.3	2.2	.87	.1	-	-	-	-	24"	7.9	6.1	2.7	1.2	.55	.2	-	-	-	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>6.9</td> <td>1.8</td> <td>1.1</td> <td>.13</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18"</td> <td>5.3</td> <td>1.8</td> <td>.9</td> <td>.68</td> <td>.13</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>4.1</td> <td>1.9</td> <td>.75</td> <td>.62</td> <td>.43</td> <td>.13</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	6.9	1.8	1.1	.13	-	-	-	-	-	18"	5.3	1.8	.9	.68	.13	-	-	-	-	24"	4.1	1.9	.75	.62	.43	.13	-	-	-
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	21.8	5.3	1.5	.1	-	-	-	-	-																																																																									
18" (as supplied)	16.6	6.3	2.2	.87	.1	-	-	-	-																																																																									
24"	7.9	6.1	2.7	1.2	.55	.2	-	-	-																																																																									
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	6.9	1.8	1.1	.13	-	-	-	-	-																																																																									
18"	5.3	1.8	.9	.68	.13	-	-	-	-																																																																									
24"	4.1	1.9	.75	.62	.43	.13	-	-	-																																																																									

Denotes fixture is compatible with incandescent or LED lamps.