




INCANDESCENT / LED 12V HYBRID PATH & SPREAD



| | 15317 AZT, BN - GLASS & METAL | 15318 AZT - GALAXY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------------------------|--|--|-----|-----|-----|-----|----|----|----|----|----|-------------|-----|-----|---|-----|-----|-----|---|---|---|--|---------------------|----|----|----|----|----|----|----|----|----|-------------|-----|-----|-----|----|----|---|---|---|---|
| Description | A sleek, modern original that combines contemporary style with smooth illumination. | Sophisticated, modern style in an understated fixture. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Ordering Guide & Finish | 15317 BN - Brushed Nickel 15317 AZT - Textured Architectural Bronze | 15318 AZT - Textured Architectural Bronze | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Housing | Aluminum (AZT) or Brass (BN) with glass diffuser | Aluminum | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Lamp Base | 12V S8 wedge base socket  | 12V S8 wedge base socket  | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Supplied Lamp | 24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA) | 24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Incandescent Lamp Options | 18.5-W(VA) 3155K (15599 CLR) | 18.5-W(VA) 3155K (15599 CLR) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LED Lamp Options | 2W (18036-18038) see page 159 Compares up to 18.5W Krypton | 2W (18036-18038) see page 159 Compares up to 18.5W Krypton | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wiring | 35" of usable #18-2, SPT-1-W leads. Cable connector supplied | 35" of usable #18-2, SPT-1-W leads. Cable connector supplied | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Mounting Acces. Included | 8" In-ground stake | 8" In-ground stake | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Optional Acces. | 15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket | 15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Integrated LED Options | 15817 – on Page 14 | NA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Notes | U.S. Patent No. D406,374 | NA | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Photometric with Supplied Lamp | <table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> <td>9'</td> </tr> <tr> <td>Footcandles</td> <td>9.4</td> <td>4.8</td> <td>2</td> <td>.72</td> <td>.32</td> <td>.16</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table> | Distance from Light | 1' | 2' | 3' | 4' | 5' | 6' | 7' | 8' | 9' | Footcandles | 9.4 | 4.8 | 2 | .72 | .32 | .16 | - | - | - | <table border="1"> <tr> <td>Distance from Light</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> <td>9'</td> </tr> <tr> <td>Footcandles</td> <td>2.6</td> <td>3.2</td> <td>1.2</td> <td>.5</td> <td>.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table> | Distance from Light | 1' | 2' | 3' | 4' | 5' | 6' | 7' | 8' | 9' | Footcandles | 2.6 | 3.2 | 1.2 | .5 | .2 | - | - | - | - |
| Distance from Light | 1' | 2' | 3' | 4' | 5' | 6' | 7' | 8' | 9' | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Footcandles | 9.4 | 4.8 | 2 | .72 | .32 | .16 | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Distance from Light | 1' | 2' | 3' | 4' | 5' | 6' | 7' | 8' | 9' | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Footcandles | 2.6 | 3.2 | 1.2 | .5 | .2 | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

 Denotes fixture is compatible with incandescent or LED lamps.