

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15391 OZ - ZEN GARDEN

15392 OZ - ZEN GARDEN BOLLARD

15319 PZ - MISSION LANTERN

Description	Path lighting with Far Eastern style and amber glass offers soft light with good spread for illuminating paths and walkways.	Bollard lighting with Far Eastern style and amber glass for soft lighting along a path.	California mission-style with frosted glass coordinates with contemporary, craftsman or Southwest architecture.																																																												
Ordering Guide & Finish	15391 OZ - Olde Bronze®	15392 OZ - Olde Bronze®	15319 PZ - Patina Bronze																																																												
Housing	Brass with textured amber seedy linen glass	Brass with textured amber seedy linen glass	Brass with satin-etched glass																																																												
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket	12V S8 wedge base socket																																																												
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)																																																												
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	N/A																																																												
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																																												
Wiring	30" of usable #18-2, SPT-1-W leads Cable connector supplied	35" of usable #18-2, SPT-1-W leads Cable connector supplied	40" of usable #18-2, SPT-1-W leads Cable connector supplied																																																												
Mounting Acces. Included	8" In-ground stake	8" In-ground stake	8" In-ground stake																																																												
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																												
Notes	U.S. Patent Pending	U.S. Patent Pending																																																													
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td><td>9'</td> </tr> <tr> <td>Footcandles</td> <td>3.2</td><td>1.2</td><td>.26</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	3.2	1.2	.26	-	-	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>.5'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>.16</td><td>.36</td><td>.20</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	.5'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	.16	.36	.20	-	-	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td><td>9'</td> </tr> <tr> <td>Footcandles</td> <td>21.1</td><td>7.3</td><td>1.7</td><td>.7</td><td>.5</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	21.1	7.3	1.7	.7	.5	-	-	-	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																						
Footcandles	3.2	1.2	.26	-	-	-	-	-	-																																																						
Distance from Light	.5'	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	.16	.36	.20	-	-	-	-	-	-																																																						
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																						
Footcandles	21.1	7.3	1.7	.7	.5	-	-	-	-																																																						

Denotes fixture is compatible with incandescent or LED lamps.