



INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15351 CO - COPPER CENTER MOUNT

15350 CO - ADJUSTABLE COPPER

Description	This classic brushed copper path light develops a natural verdigris patina over time.	Shade adjusts up or down. This traditional style light offers versatility in light spread and will develop a natural verdigris patina over time.																																																												
Ordering Guide & Finish	15351 CO - Unfinished Copper	15350 CO - Unfinished Copper																																																												
Housing	Copper (Copper will naturally patina over time)	Copper (Copper will naturally patina over time)																																																												
Lamp Base	12V S8 wedge base socket 	12V S8 wedge base socket																																																												
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																																												
Incandescent Lamp Options	18.5-W(VA) (15599 CLR)	18.5-W 3155K (15599 CLR)																																																												
LED Lamp Options	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	N/A																																																												
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connector supplied	21" of usable #18-2, SPT-1-W leads. Cable connector supplied																																																												
Mounting Acces. Included	8" In-ground stake	8" In-ground stake																																																												
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																												
Notes	N/A	N/A																																																												
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>Stern Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>18"</td> <td>10.4</td> <td>5.2</td> <td>1.9</td> <td>.83</td> <td>.23</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stern Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	18"	10.4	5.2	1.9	.83	.23	-	-	-	-	<table border="1"> <thead> <tr> <th>Shade Position on Stern</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>Bottom</td> <td>6.4</td> <td>5.0</td> <td>2.3</td> <td>1.0</td> <td>.4</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>Middle</td> <td>6.3</td> <td>2.7</td> <td>2.0</td> <td>.9</td> <td>.4</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>Top</td> <td>6.0</td> <td>2.4</td> <td>.8</td> <td>.3</td> <td>.1</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Shade Position on Stern	1'	2'	3'	4'	5'	6'	7'	8'	9'	Bottom	6.4	5.0	2.3	1.0	.4	.1	-	-	-	Middle	6.3	2.7	2.0	.9	.4	.1	-	-	-	Top	6.0	2.4	.8	.3	.1	-	-	-	-
Stern Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																					
18"	10.4	5.2	1.9	.83	.23	-	-	-	-																																																					
Shade Position on Stern	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																					
Bottom	6.4	5.0	2.3	1.0	.4	.1	-	-	-																																																					
Middle	6.3	2.7	2.0	.9	.4	.1	-	-	-																																																					
Top	6.0	2.4	.8	.3	.1	-	-	-	-																																																					

 Denotes fixture is compatible with incandescent or LED lamps.