

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15379 OZ - GATE HOUSE™

15446 OZ - ARIES MANOR™

15447 OZ - ARIES MANOR™

Description	Classic estate styling.	An elegant and stately path light featuring solid brass construction, a turned spindle stem.	An elegant and stately indirect path light featuring solid brass construction and a turned spindle stem.
Ordering Guide & Finish	15379 OZ - Olde Bronze®	15446 OZ - Olde Bronze®	15447 OZ - Olde Bronze®
Housing	Cast Brass	Brass with cocoa turned marble accent. Citrine glass.	Brass with cocoa turned marble accent.
Lamp Base	12V S8 wedge base socket	12V T5 wedge base socket	12V T5 wedge base socket
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)
LED Lamp Options	2W (18036-18038) see page 159 Compares up to 18.5W Krypton	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon
Wiring	34" of usable #18-2, SPT-1-W leads Cable connector supplied	24" of usable #18-2, SPT-1-W leads Cable connector supplied	24" of usable #18-2, SPT-1-W leads Cable connector supplied
Mounting Acces. Included	14" In-ground stake	8" In-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Notes	U.S. Patent No. D561,371	N/A	N/A
Photometric with Supplied Lamp	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'
	Footcandles 8.16 3.43 3.43 1.46 .33 - - - -	Footcandles 0.5 1.1 0.8 0.4 0.1 0 - - - -	Footcandles 6.9 4.9 2.9 1.3 0.4 0.1 - - - -

Denotes fixture is compatible with incandescent or LED lamps.