



15810 AZT, BBR, BE, BKT - LED DOME PATH LIGHT

15811 AZT, BE - LED DOME PATH LIGHT - SHORT STEM

Description	Now in Design Pro LED, a wider path and spread light that is unobtrusive in the landscape. Coordinates with the 15811 and 15870 path and spread fixtures.	A shorter version of our LED 15810 designed for use in lower planting and smaller garden areas.
Ordering Guide & Finish	15810 AZT - Textured Architectural Bronze (Marine grade powder coat) 15810 BBR - Bronzed Brass 15810 BE - Beach (Marine grade powder coat) 15810 BKT - Textured Black (Marine grade powder coat)	15811 AZT - Textured Architectural Bronze (Marine grade powder coat) 15811 BE - Beach (Marine grade powder coat)
Housing	Cast Aluminum, Cast Brass	Cast Aluminum
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Total Lumens & Efficacy	3000K = 140 Lm 3000K= 35 Lm/W	3000K = 140 Lm 3000K= 35 Lm/W
Wiring	30" of useable #18-2, SPT-1W leads. Cable connector supplied	36" of useable #18-2, SPT-1W leads. Cable connector supplied
Mounting Acces. Included	8" in-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Incandescent	15310 - on page 98	15410 - on page 99
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers
Fixture Photometric (fc)	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 6.47 5.50 3.82 2.20 1.44 1.07 .097 0.55 0.32	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 12.18 11.57 6.07 3.17 1.88 1.05 0.45 0.36 0.27