

# KICHLER®


PROJECT:
TYPE:
ORDERING # :
COMMENTS:

## LED Side Mount Cast Brass







## FEATURES

- LED technology is combined with premium solid brass material, engineered to withstand harsh coastal conditions. Coordinates with matching LED deck light 15765.
- Cast Brass Housing.
- High-Low Setting – Low: 2.5 W / 4 VA Light Output, High: 4 W / 5.8 VA Light Output
- Integrated LEDs and Driver, 2950K (-150/+175), High CRI.
- 9V - 15V AC/DC
- 35" of usable #18-2, SPT-1-W leads. Cable connector supplied.
- 8" In-ground stake



## ORDERING INFORMATION

EXAMPLE: 15827BBR (Product # & Finish)

PRODUCT	FINISH	WATTAGE	LIGHT SOURCE	WIRING	MOUNTING ACCESSORIES (INCLUDED)	OPTIONS & ACCESSORIES																																								
<b>15827</b> Dimensions: 7" W x 20.5" L	<b>Cast Brass</b> <b>BBR - Bronzed Brass</b> 	Low Setting: 2.5 W / 4 VA High Setting: 4 W / 5.8 VA  <b>Note:</b> Not for use with electronic transformers.	Integrated LEDs and Driver 2950K (-150 / +175) High CRI	35" of usable #18-2, SPT- 1-W leads.  Cable connector supplied.	8" In-ground stake	<b>15601AZT</b> - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal <b>15601BKT</b> - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal <b>15601BBR</b> - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal    <b>Flange For Tree / Surface Mounting</b> <b>15607AZT</b> - Textured Bronze Finish <b>15607BKT</b> - Textured Black Finish <b>15607BBR</b> - Bronzed Brass Finish    <b>Polycarbonate Lens</b> <b>15677CLR</b> - Accessory lens of clear polycarbonate plastic. Provides additional internal protection from lawn sprinklers, etc.  																																								
<p>Fixture Photometric (fc)– High Setting</p> <table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>31.5</td> <td>17.2</td> <td>6.7</td> <td>2.5</td> <td>1.2</td> <td>0.5</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table> <p>Fixture Photometric (fc) – Low Setting</p> <table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>							Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	31.5	17.2	6.7	2.5	1.2	0.5	-	-	-	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles									
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																					
Footcandles	31.5	17.2	6.7	2.5	1.2	0.5	-	-	-																																					
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																					
Footcandles																																														

## NOTES

**For Warranty Information, please visit [www.landscapelighting.com](http://www.landscapelighting.com)**

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.

