



	15833 AZT - LED BROAD ROOF	15804 AZT - LED TAPERED COLUMN																																								
<b>Description</b>	A sculpted spindle center is capped by a broad, shallow roof that diffuses and spreads LED light.	A tapered column rises to a narrow point and then widens to expose LED illumination emanating from the reverse taper cap.																																								
<b>Ordering Guide &amp; Finish</b>	15833 AZT - Textured Architectural Bronze (Marine grade powder coat)	15804 AZT - Textured Architectural Bronze (Marine grade powder coat)																																								
<b>Housing</b>	Cast Aluminum	Cast Aluminum																																								
<b>Light Source</b>	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver																																								
<b>Color Temp. (CCT) &amp; CRI</b>	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI																																								
<b>Power Usage at 12V AC Input VA and Watts</b>	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	1 W, 1.7 VA Multiply fixture VA by the number of fixtures used to determine size of transformer																																								
<b>Operating Voltage Range</b>	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology																																								
<b>Lumen Maint.</b>	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours																																								
<b>Total Lumens &amp; Efficacy</b>	3000K = 140 Lm 3000K = 35 Lm/W	3000K = 140 Lm 3000K = 35 Lm/W																																								
<b>Wiring</b>	30" of usable #18-2, SPT-1-W leads. Cable connector supplied	30" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
<b>Mounting Acces Included</b>	8" in-ground stake	8" in-ground stake																																								
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
<b>Notes</b>	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers																																								
<b>Fixture Photometric (fc)</b>	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>13.5</td><td>3.7</td><td>0.8</td><td>0.3</td><td>0.2</td><td>0.1</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	13.5	3.7	0.8	0.3	0.2	0.1	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>7.2</td><td>3.5</td><td>1.4</td><td>0.8</td><td>0.5</td><td>0.3</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	7.2	3.5	1.4	0.8	0.5	0.3	-	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	13.5	3.7	0.8	0.3	0.2	0.1	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	7.2	3.5	1.4	0.8	0.5	0.3	-	-	-																																	