

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15437 TZT - PIERCED SCROLLWORK

15330 OZ - ADJUSTABLE CRESENT

Description	Classic style scrollwork is pierced and shaped into a pyramid allowing the light to play against the sculpted textures.	Adjustable shade on this versatile fixture allows it to be used as a path or accent light or for wall washing.																																								
Ordering Guide & Finish	15437 TZT - Textured Tannery Bronze™	15330 OZ - Olde Bronze®																																								
Housing	Cast Aluminum	Brass																																								
Lamp Base	12V T5 wedge base socket	12V S8 wedge base socket																																								
Supplied Lamp	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																								
Incandescent Lamp Options	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	18.5-W(VA) 3155K (15599 CLR)																																								
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18036-18038) see page 159 Compares up to 18.5W Krypton																																								
Wiring	24" of usable #18-2, SPT-1-W leads. Cable connector supplied	42" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
Mounting Acces. Included	8" In-ground stake (Included)	8" In-ground stake (Included)																																								
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>11.04</td><td>6.99</td><td>3.14</td><td>1.56</td><td>0.44</td><td>0.10</td><td>0.05</td><td>0.03</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	11.04	6.99	3.14	1.56	0.44	0.10	0.05	0.03	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>15.18</td><td>9.98</td><td>4.13</td><td>1.52</td><td>.6</td><td>.22</td><td>.03</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	15.18	9.98	4.13	1.52	.6	.22	.03	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	11.04	6.99	3.14	1.56	0.44	0.10	0.05	0.03	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	15.18	9.98	4.13	1.52	.6	.22	.03	-	-																																	

Denotes fixture is compatible with incandescent or LED lamps.