

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15421 AGZ - COTSWOLD™ CONVERTIBLE HEIGHT TIKI

15449 TZT - CATHEDRAL BOLLARD

Description	Adjustable-height stem converts path light to a Tiki torch style for use around patios, barbecue grills or outdoor dining areas.	Cathedral arches and interwoven bands created to form a transitional stanchion for the garden's edge.
Ordering Guide & Finish	15421 AGZ - Aged Bronze	15449 TZT - Textured Tannery Bronze™
Housing	Cast Aluminum with weathered white glass	Aluminum with dark citrine glass
Lamp Base	12V T5 wedge base socket	12V T5 wedge base socket
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.26-W(VA)	11.6-W(VA) 912X (17023) (2) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021) (2 required)
LED Lamp Options	2W (18039-18041) see page 159 Compares up to 16W Xenon	2W (18039-18041) see page 159 Compares up to 16W Xenon
Wiring	24" of usable #18-2, SPT-1-W leads at high position. 50" usable leads at low position. Cable connector supplied	22" of usable #18-2, SPT-1-W leads. Cable connector supplied
Mounting Acces. Included	14" In-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	N/A
Photometric with Supplied Lamp	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' (at 32" height) Footcandles .25 .3 .2 .1 - - - - -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 0.44 1.81 1.26 0.70 0.39 0.25 0.16 .012 0.10

Denotes fixture is compatible with incandescent or LED lamps.