

KOHLER® Roughing-In

K-1106, K-1106-L, K-1106-R
PROFLEX® 6032
BATH WHIRLPOOL

Product Information

Applicable products:	
Bath whirlpool – drop-in	K-1106
Bath whirlpool – tile flange, left drain	K-1106-L
Bath whirlpool – tile flange, right drain	K-1106-R
Product is ADA compliant when installed with seat at head end ADA	

Fixture*:	
Basin area:	
Bottom area	46" (116.8 cm) x 20" (50.8 cm)
Top area	55" (139.7 cm) x 22" (55.9 cm)
Weight	49 lbs (22 kg)
To overflow:	
Water depth	12-1/2" (31.8 cm)
Capacity	49 gal (185 L)
* Approximate measurements for comparison only.	

Pump:	V	Hz	A
1-speed	120	60	7.5

Required Electrical Service

Dedicated circuit required, protected with a Class A Ground-Fault Circuit-Interrupter (GFCI):	
Pump/control	120 V, 15 A, 60 Hz
Locate the outlet behind the whirlpool and within 24" (61 cm) of the pump.	

Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 36 lbs/square foot (177 kg/square meter) loading.

The apron must be installed before the finished floor and wall materials.

This fixture conforms to ANSI Standard Z124.1.2. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-11677 or K-11677M)

