

# KOHLER® Roughing-In

## K-1849-G, K-1849-GCR UNDERSCORE® BUBBLEMASSAGE™ BATH

### Product Information

Applicable product:	
BubbleMassage bath – without chromatherapy	K-1849-G
BubbleMassage bath – with chromatherapy (shown)	K-1849-GCR

Fixture*:	
Bathing well:	
Basin area, bottom	39-9/16" (1005 mm) x 24-11/16" (627 mm)
Basin area, top	53-5/8" (1362 mm) x 29-1/2" (749 mm)
Weight	100 lbs (45.4 kg)
To overflow:	
Water depth	17-1/8" (435 mm)
Capacity	81.1 gal (307 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	59-1/2" (1511 mm) x 35-1/2" (902 mm)
-----------------	--------------------------------------

Blower motor/control:	Heater	V	Hz	A
	300 W	220-240	50/60	15

Required accessories:	
Clearflo slotted overflow brass bath drain <b>OR</b>	K-7271
Clearflo slotted overflow bath drain – PVC pipe	K-7272

### Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD):	
Blower motor/control:	220-240 V, 15 A, 50/60 Hz

### Installation Notes

Install this product according to the installation guide.

Floor support under bath must provide for a minimum of 54 lbs/square foot (263 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

Fixture conforms to ANSI Standards Z124.1.2. All dimensions are nominal.

