

# KOHLER® Roughing-In

**K-3753**  
**PERSUADE® CIRC**  
**DUAL FLUSH TOILET**

## Product Information

Applicable product:	
Dual flush toilet – center push button	K-3753
Fixture:	
Configuration	two-piece, elongated
Water per flush	1.6 gpf (6 lpf) or 1.0 gpf (3.8 lpf)
Passageway	2" (5.1 cm)
Water area	4-1/2" (11.4 cm) x 5-3/4" (14.6 cm)
Water depth from rim	8-1/2" (21.6 cm)
Seat post hole centers	5-1/2" (14 cm)
Included components:	
Bowl	K-4353
Tank	K-4442
Tank cover	1101883
Push buttons	1072961

## Installation Notes

**IMPORTANT!** The rough-in must be 12" (30.5 cm) or more from the base of the wall or baseboard. Install or relocate the supply and outlet as necessary to conform to rough-in dimensions.

If this toilet is installed to new construction, install a new supply stop following the dimensions in the diagram.

In installations with the supply stop installed, the existing supply stop may need to be relocated if it is less than 8-1/2" (21.6 cm) from the centerline of the toilet. Dry fit the toilet to confirm if the supply stop needs to be relocated.

The supplied hose will extend roughly 6" (15.2 cm) from the toilet. If the supplied hose does not reach the supply stop, a longer supply hose may be used.

Fixture conforms to ASME Standard A112.19.2/CSA B45.1. All dimensions are nominal.

