

KOHLER®

Roughing-In

K-7516, K-7517
ELECTRONIC FAUCET

Product Information

Applicable product:	
Electronic faucet – without mixer	K-7516
Electronic faucet – with mixer	K-7517
Product is ADA, CSA B651, OBC compliant.	
Optional accessories:	
Grid drain with overflow	K-7129-A
Grid drain without overflow	K-7129
4" (10.2 cm) escutcheon plate – square	K-13478-B
8" (20.3 cm) escutcheon plate – square	K-13479-B
Thermostatic mixing valve	K-13601

Installation Notes

Install this product according to the installation guide.

A 1-1/4" (3.2 cm) minimum to 1-1/2" (3.8 cm) maximum diameter mounting hole is required.

The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (4.4 cm). This will allow proper clearance for setscrew access.

The maximum distance between the lavatory basin edge to the base of the faucet spout must be 1-3/4" (4.4 cm).

The maximum height of the lip basin should be 3/4" (1.9 cm).

Product includes 0.5 gpm (1.9 lpm) rosebud spray aerator. Other aerator styles are available. Please contact your distributor or see Kohler.com.

This product requires a 30-year Hybrid Energy Cell (included).

ADA, CSA B651, OBC compliant when installed to the specific requirements of these regulations.

