

KOHLER® Roughing-In

K-1239-G, K-1239-GLF, K-1239-GRF MARIPOSA® 5' BUBBLEMASSAGE™ BATH

Product Information

Applicable products:	
5' Bubblemassage bath – drop-in (shown)	K-1239-G
5' Bubblemassage bath – 3-side integral flange, left drain	K-1239-GLF
5' Bubblemassage bath – 3-side integral flange, right drain	K-1239-GRF

Fixture*:	
Bathing well:	
Basin area, bottom	46" (1168 mm) x 24" (610 mm)
Basin area, top	54" (1372 mm) x 27" (686 mm)
Weight	100 lbs (45.4 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	63 gal (238.5 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	58" (1473 mm) x 34" (864 mm)
-----------------	------------------------------

Blower motor:	Heater	V	Hz	A
	300 W	120	60	5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Blower motor:	120 V, 15 A, 60 Hz
Blower motor is supplied with a 24" (610 mm) grounding-type plug-in cord.	

Installation Notes

Install this product according to the installation guide.

NOTICE: If the blower motor and check valve are relocated, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under the bath must provide for a minimum of 43.5 lbs/square foot (212.6 kg/square meter) loading.

If used, the optional apron must be installed before the finished floor and wall materials are installed.

Fixture conforms to CSA B45.5/IAPMO Z124. All dimensions are nominal.

