

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more.

**CONSTRUCTION** — This contemporary shaped fixture features a matte white acrylic diffuser and white aluminum housing.

**OPTICS** — Produces 660 lumens at 50,000 hours life.

**ELECTRICAL** — Fixture operates at 120 volts, 60 Hz. Standard input = 9.3 watts, 70 lumens per watt. Works with most standard incandescent dimmers (see list of approved dimmers).

**INSTALLATION** — All mounting hardware included.

**LISTINGS** — CSA certified to US and Canadian standards and listed suitable for damp locations.

**WARRANTY** — 5-year limited warranty. Complete warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor

# Versi Lite™ 7" LED Flush



HIGH-PERFORMANCE LED



### Specifications

Height: 1-3/4 (4.4)

Width: 7-1/4 (18.4)

All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

**Example: FMML 7 840**

FMML	7				
Series	Size	CRI	Color temperature		
<b>FMML</b> LED Versi Lite	<b>7</b> 7" diameter	<b>8</b> >80 CRI	<b>40</b> 4000K	30 3000K	27 2700K

LIGHTING FACTS


Lithonia Lighting

**Light Output (Lumens)** **659**

**Watts** **9.36**

**Lumens per Watt (Efficacy)** **70**

**Color Accuracy** **85**

Color Rendering Index (CRI)

**Light Color** **4043 (Bright White)**

Correlated Color Temperature (CCT)



2700K   3000K   4500K   6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the *Label Reference Guide*.

Registration Number: NJSM-W7QK8W (12/14/2012)  
Model Number: FMML 7 840  
Type: Surface-mounted fixture (other)

Suggested Dimmers	
The FMML is designed to operate with most standard Triac Based (Forward Phase-Control or Leading Edge) dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.	
Manufacturer	Part Number (s)
Leviton	6633P
Leviton	IPL06
Leviton	6674P
Leviton	IPE04
Leviton	Trimatron 600W
Lutron	DVELV 300P
Lutron	Skylark 300P
Lutron	NTELV 300
Lutron	NLV 600
Synergy	ISD 600 I 120

PHOTOMETRICS

FMML 7 840, 655.7 delivered lumens, test no. LTL22758, tested in accordance to IESNA LM-79.

