

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and much more.

CONSTRUCTION — This contemporary shaped fixture features a matte white acrylic diffuser and white or textured bronze aluminum housing.

OPTICS — Produces the following lumens at 50,000 hours life:

- 2700K 612 lumens
- 3000K 642 lumens
- 4000K 660 lumens

ELECTRICAL — Fixture operates at 120 volts, 60 Hz. Standard input = 9.3 watts, 70 lumens per watt.

Works with most standard incandescent dimmers (see list of suggested dimmers on page 2).

INSTALLATION — All mounting hardware included.

LISTINGS — CSA certified to US and Canadian standards and listed suitable for damp or wet locations. U.S. Patent No. D691,763

WARRANTY — 5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Specifications subject to change without notice.

Decorative Indoor

Versi Lite™ 7" LED Flush



HIGH-PERFORMANCE LED




Specifications

Height: 1-3/4 (4.4)

Width: 7-1/4 (18.4)

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

For shortest lead times, configure product using **standard options (shown in bold)**.

Example: FMML 7 840 WL

Series	Size	CRI	Color temperature	Fixture finish	Option
FMML LED Versi Lite flushmount	7 7" diameter	8 >80	40 4000K (660 lumens) 30 3000K (642 lumens) 27 2700K (612 lumens)	(blank) White DDBT Textured bronze	WL Wet location

LIGHTING FACTS

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) **612**
Watts **10.35**
Lumens per Watt (Efficacy) **59**

Color Accuracy
Color Rendering Index (CRI) **85**

Light Color
Correlated Color Temperature (CCT) **2700 (Warm White)**

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: NJSM-9ECDFF (7/19/2013)
Model Number: FMML 7 827
Type: Surface-mounted fixture (other)

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) **642**
Watts **10.2**
Lumens per Watt (Efficacy) **63**

Color Accuracy
Color Rendering Index (CRI) **85**

Light Color
Correlated Color Temperature (CCT) **3000 (Bright White)**

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: NJSM-B45YJQ (7/19/2013)
Model Number: FMML 7 830
Type: Surface-mounted fixture (other)

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) **659**
Watts **9.4**
Lumens per Watt (Efficacy) **70**

Color Accuracy
Color Rendering Index (CRI) **85**

Light Color
Correlated Color Temperature (CCT) **4000 (Bright White)**

2700K 3000K 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: NJSM-QSEG7G (8/6/2013)
Model Number: FMML 7 840 [UPGRADE 07/2013]
Type: Luminaire - Other

Suggested Dimmers

The FMML is designed to operate with most standard Triac Based (Forward Phase-Control or Leading Edge) dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.

Manufacturer	Part Number (s)	Manufacturer	Part Number (s)
Leviton	6633P	Lutron	DVELV 300P
Leviton	IPL06	Lutron	Skylark 300P
Leviton	6674P	Lutron	NTELV 300
Leviton	IPE04	Lutron	NLV 600
Leviton	Trimatron 600W	Synergy	ISD 600 I 120

PHOTOMETRICS

FMML 7 test no. LTL22758, tested in accordance to IESNA LM-79.

