

TSEA60[™] 1-piece

60" x 34" x 77" | 1524 x 864 x 1956 mm



Codes/Standards Applicable

- ANSI Z124.1.2
- CSA B45 Series

Whirlpool Tub Showers:

- UL1795
- ASME A112.19.7
- CSA C22.2 No. 218.3-93
- CSA B45.10

STANDARD FEATURE(S)

Built-in shelf Towel bar

PLUMBER FEATURE(S)

Right or left-hand drain, specify when ordering One-piece installation

Colors

Standard Fiberglass Colors



Non-Standard Fiberglass Colors



Colors shown are for reference purposes only and are subject to change without notice. Exact matches are not possible with your monitor display or printing method used.

TSEA60[™] 1-piece

Here are the electrical specifications for all MAAX Professional tub shower therapeutic systems offered in the United States.

PLEASE NOTE THAT SOME SYSTEMS MAY NOT BE AVAILABLE ON THE PRODUCT YOU HAVE SELECTED.

Please refer to the Common Options and Massage System(s) sections for more details.

WHIRLPOOL		
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).		
Heater: Requires a dedicated circuit protected by a Class GFCI.		
Pump	3/4HP / 120V / 7.5A / 60Hz	
Heater	1500W / 120V / 12.5A / 60Hz	

AEROEFFECT WITH AIR PUSH CONTROL	
Blower: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).	
Blower	1.4 HP / 120V / 9.5A / 60Hz

COMBINED WHIRLPOOL / AEROEFFECT WITH AIR PUSH CONTROL (W/A)		
Blower: Requires a dedicated circuit protected by a Class A GFCI.		
Pump: Requires a dedicated circuit protected by a Class A GFCI. This circuit can be shared with Chromatherapy (option).		
Heater: Requires a dedicated circuit protected by a Class A GFCI.		
Blower	1.4 HP / 120V / 9.5A / 60Hz	
Pump	3/4HP / 120V / 7.5A / 60Hz	
Heater	1500W / 120V / 12.5A / 60Hz	

CHROMATHERAPY

Requires a dedicated circuit protected by a Class A GFCI.

Installation Note

Install this product according to the Installation Guide.

All electrical wiring must be done per national/local electrical codes.