

## Lighting Your Life Since 1970

Product Specifications - 10124ICSN		
Job Name:	Job Type:	
Quantity:	Comments	



### 10124ICSN

**Basix 5-Light Chandelier** 

**Finish** Satin Nickel

Glass/Shade

Ice

**Product Category** Down Light Chandelier

Lamping	
Number of	Bulb
<b>Light Type</b>	

Bulb Type         Mil           Max Bulb Wattage         10           Max Fixture Wattage         50           Rated Life         ±2,500 Hour           Rated Lumens         ±5,75           Color Temp         ±2,700 Bulb(s)           Bulb(s)         Not Include           Light Up/Down         N//           Beam Spread         N//           CRI         N//           Photo Cell Included         N//           Ballast/Driver/Transformer         N//	Number of Bulbs	5
Max Bulb Wattage         10           Max Fixture Wattage         50           Rated Life         ±2,500 Hour           Rated Lumens         ±5,75           Color Temp         ±2,700 Hour           Bulb(s)         Not Included           Light Up/Down         N//           Beam Spread         N//           CRI         N//           Photo Cell Included         N//           Ballast/Driver/Transformer         N//	Light Type	Incandescent
Max Fixture Wattage         50           Rated Life         ±2,500 Hour           Rated Lumens         ±5,75           Color Temp         ±2,700 Hour           Bulb(s)         Not Included           Light Up/Down         N//           Beam Spread         N//           CRI         N//           Photo Cell Included         N//           Ballast/Driver/Transformer         N//	Bulb Type	MB
Rated Life         ±2,500 Hour           Rated Lumens         ±5,75           Color Temp         ±2,700 Not Included           Bulb(s)         Not Included           Light Up/Down         N//           Beam Spread         N//           CRI         N//           Photo Cell Included         N//           Ballast/Driver/Transformer         N//	Max Bulb Wattage	100
Rated Lumens ±5,75 Color Temp ±2,700 Not Include Light Up/Down N// Beam Spread N// CRI N// Photo Cell Included N// Ballast/Driver/Transformer N	Max Fixture Wattage	500
Color Temp ±2,700 l Bulb(s) Not Include Light Up/Down N// Beam Spread N// CRI N// Photo Cell Included N// Ballast/Driver/Transformer N	Rated Life	±2,500 Hours
Bulb(s) Not Included Light Up/Down N// Beam Spread N// CRI N// Photo Cell Included N// Ballast/Driver/Transformer No	Rated Lumens	±5,750
Light Up/Down N// Beam Spread N// CRI N// Photo Cell Included N// Ballast/Driver/Transformer N//	Color Temp	±2,700 K
Beam Spread N// CRI N// Photo Cell Included N// Ballast/Driver/Transformer N	Bulb(s)	Not Included
CRI N// Photo Cell Included N// Ballast/Driver/Transformer N	Light Up/Down	N/A
Photo Cell Included N// Ballast/Driver/Transformer N	Beam Spread	N/A
Ballast/Driver/Transformer N	CRI	N/A
	Photo Cell Included	N/A
<b>Dimmable</b> Standar	Ballast/Driver/Transformer	No
	Dimmable	Standard

Measurements	
Width	

25.0"
21.0"
N/A
12.0 lbs
N/A
N/A
36"
180"
N/A
N/A
N/A

Shipping	
Carton Weight	12.0 lbs
Carton Width	17"
Carton Height	10"
Carton Length	24"
Carton Cubic Feet	2.30
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification		Other	
Safety Rating	Dry	UPC Code	783209025868
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Iron

# **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.