

## Lighting Your Life Since 1970

Product Specifications - 21158WHUB			
Job Name:	Job Type:		
Quantity:	Comments		



## 21158WHUB

## **Mondrian 6-Light Entry Foyer Pendant**

**Finish** 

Umber Bronze

Glass/Shade

**Product Category** 

Entry Foyer Pendant

Lamping	
Number of Bulbs	6
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	360
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	21.0"
Height	44.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	17.3 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	17.3 lbs
Carton Width	21"
Carton Height	40"
Carton Length	24"
Carton Cubic Feet	11.50
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Oversize

Safaty Bating	Day IIBC Code	703
Certification	Other	

Certification		Other	
Safety Rating	Dry	UPC Code	783209083806
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	Yes
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents	
Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.