

Lighting Your Life Since 1970

Product Specifications - 23077CLFTPC		
Job Name:	Job Type:	
Quantity:	Comments	
	,	



23077CLFTPC

27.0" 7.0" N/A N/A

N/A

N/A

Silo 6-Light Chandelier

Polished Chrome

Lamping

Lamping	
Number of Bulbs	6
Light Type	Xenon
Bulb Type	G9 Frost
Max Bulb Wattage	75
Max Fixture Wattage	450
Rated Life	±2,000 Hours
Rated Lumens	±7,800
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade
Clear/Frosted

Canopy Height

Canopy Length

Measurements	
Width	
Height	
Length	
Extension	
Back Plate Width	

N/A **Back Plate Height** N/A HCO N/A Min Overall Height N/A Max Overall Height 130.0" Hanging Weight 11.4 lbs Height Adjustable Yes Slope N/A **Chain Length** N/A Wire Length 180" **Canopy Width** N/A

Product Category

Single-Tier Chandelier

Shipping	
Carton Weight	11.4 lbs
Carton Width	26"
Carton Height	7"
Carton Length	30"
Carton Cubic Fo	eet 3.15
Master Pack	1
Master Pack We	eight N/A
Master Pack Wi	dth N/A
Master Pack He	ight N/A
Master Pack Le	ngth N/A
Master Cubic Fo	eet N/A
UPS Shippable	Yes

Certification	Other

Certification		Other	
Safety Rating	Dry	UPC Code	783209086739
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Metal

		-1-	4-
	uiv		
-4	uiv	uic	,,,,

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.