



Lighting Your Life Since 1970

## Product Specifications - 23078CLFTPC

Job Name:	Job Type:
Quantity:	Comments:



## 23078CLFTPC Silo 8-Light Chandelier

**Finish**  
Polished Chrome

**Glass/Shade**  
Clear/Frosted

**Product Category**  
Single-Tier Chandelier

### Lamping

Number of Bulbs	8
Light Type	Xenon
Bulb Type	G9 Frost
Max Bulb Wattage	75
Max Fixture Wattage	600
Rated Life	±2,000 Hours
Rated Lumens	±10,400
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

### Measurements

Width	32.0"
Height	7.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	130.0"
Hanging Weight	15.0 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	180"
Canopy Width	8.8"
Canopy Height	N/A
Canopy Length	N/A

### Shipping

Carton Weight	15.0 lbs
Carton Width	32"
Carton Height	8"
Carton Length	32"
Carton Cubic Feet	4.51
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

### Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No
Dark Sky	N/A

### Other

UPC Code	783209086746
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Metal

### Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.