

Lighting Your Life Since 1970

Glass/Shade

Product Specifications - 872120I						
Job Name:	Job Type:					
Quantity:	Comments					

Product Category



Finish

87212OI

Rim EE 2-Light Flush Mount

Oil Rubbed Bronze		White		Flush Mount	
Lamping		Measurements		Shipping	
Number of Bulbs	1+1	Width	21.0"	Carton Weight	3.8 lbs
Light Type	Fluorescent	Height	3.0"	Carton Width	4"
Bulb Type	4-Pin T9 Circline	Length	N/A	Carton Height	21"
Max Bulb Wattage	32+40	Extension	N/A	Carton Length	21"
Max Fixture Wattage	72	Back Plate Width	N/A	Carton Cubic Feet	1.13
Rated Life	15000+18000	Back Plate Height	N/A	Master Pack	4
Rated Lumens	±4,750	НСО	N/A	Master Pack Weight	17.3 lbs
Color Temp	±3,100 K	Min Overall Height	N/A	Master Pack Width	17.9"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	22.1"
Light Up/Down	N/A	Hanging Weight	3.8 lbs	Master Pack Length	21.7"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	4.96
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	No	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		3,13			
Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209048652	Incandescent Watts	432
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	Yes	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		
			5,00.		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.