

### Lighting Your Life Since 1970

	Product Specifications - 85053HOVR			
Jo	ob Name:	Job Type:		
Q	uantity:	Comments		



#### 85053HOVR

Coldwater EE 1-Light Outdoor Wall Lantern

**Finish** Glass/Shade **Product Category** Outdoor Wall Mount Acid Verde Honey

Lamping	
Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	18
Max Fixture Wattage	18
Rated Life	±10,000 Hours
Rated Lumens	±1,355
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	Yes
Ballast/Driver/Transformer	No
Dimmable	N/A

,	
Measurements	

weasurements	
Width	6.0"
Height	12.0"
Length	N/A
Extension	9"
Back Plate Width	4.5"
Back Plate Height	9.5"
HCO	3"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.3 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

## Shinning

Snipping	
Carton Weight	3.3 lbs
Carton Width	8"
Carton Height	14"
Carton Length	12"
Carton Cubic Feet	0.74
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

#### Certification Other

00.0			
UL Standard	Wet	UPC Code	783209023185
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Aluminum

# **Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.