

Specifications

FAUCET DESCRIPTION

- Metal construction with either chrome plated, decorative glacier, lvory brushed platinum or sand finishes
- 1/2" IPS connections will accept standard ball nose connection for 3/8" tubing

OPERATION

- Lever style handle
 - Temperature controlled by 180° arc of handle travel
- Will operate with less than 5lbs. of force

FLOW

• Aerator is limited to 2.2 gpm max (8.3 L/min) CARTRIDGE


• 1225 cartridge design (not 1200)

Nonmetallic/nonferrous and stainless steel material
STANDARDS

- Designed and manufactured to comply with the requirements of: CSA B-125, ASME A112.18.1M, and all applicable requirements referenced therein and complies with the applicable requirements of ANSI A117.1.
- Certified to ANSI/NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe Water Drinking Act

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



CHATEAU[®] Single-Handle Kitchen Faucet

Models: 7425,7425S,7425SLP, 7425V, 7425W, 87425

Bulk Model: 67425 (bulk packed 12 per carton)

> NOTE: See reverse side for illustrated parts

NOTE: DESIGNED TO INSTALL THROUGH 3 HOLES 1-1/4" (32mm) MIN. DIA. AND 4" (102mm) ON CENTER.

