

DESCRIPTION

- Metal construction with, a chrome plated, LifeShine® polished brass, black opal, classic gold, platinum, satine or glacier finish
- Pressure balancing cycle valve design with an adjustable temperature limit stop
- 1/2" CC connections

OPERATION

- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to $\pm 2^\circ$

CARTRIDGE


- 1222 cartridge design
- Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations

STANDARDS

- Third party certified by CSA to meet CSA B-125, ASME A112.18.1M and all applicable requirements referenced therein and complies with the applicable requirements of ANSI A117.1

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations




MONTICELLO® POSI-TEMP® Single Handle Tub/Shower (Trim Only)

Models: T2343, T2343P, T2343W
(Bulk Packed 12 per carton)

**RT2343, RT2343BP, RT2343CG,
RT2343P, RT2343PM, RT2343ST
T2442, T2442CP, T2442CPC, T2442P, T2442W**
(Packed 1 per carton)

**NOTE: See reverse side for illustrated
parts and optional handle inserts**



CRITICAL DIMENSIONS

(DO NOT SCALE)



ADA symbol applies to shower valve control only.