Product Name & Number:	**Pacific Bamboo – WEL11**
Collection:	**Rarity**
Construction:	**Engineered**
Face Species:	**Bamboo (Bambusodae)**
Core Species:	Poplar
Number of Plies:	**6**
Thickness:	**3/8”**
Width:	**3”**
Grade:	Select & Better
Profile:	**Kissed Edges/Square Ends**
Face Finish:	**Smooth**
Finish Treatment:	**CrystalShield Aluminum Oxide**
Gloss Level:	60° + or - 5°
Sq. Ft. per Carton:	24
Sq. Ft. per Pallet:	**960**
Cartons per Pallet:	40
Weight per Carton:	**32.13 lbs**
Weight per Pallet:	**1285.2 lbs**
Installation:	**Direct Glue/Nail/Staple/Float** **On/Above/Below Grade** **Wood/Concrete Subfloor** **No Radiant Heat**
Warranties:	**25 year Finish** **Lifetime Structure** **Lifetime Moisture**
Smoke Density:	**Under 450**
Janka Hardness:	**Not Applicable**
Photo Sensitivity:	**2**
Character Variation:	**Low**
Critical Radiant Flux:	
Direct Glue:	**Class 2**
Mechanically Attached:	**Class 2**
Floating:	
Static Coefficient of Friction:	
Dry:	**.69**
Wet:	**.60**
Sound Transmission (STC):	
MoistureGuard:	**53**
SilentGuard:	**54**
Impact Insulation Class (IIC):	
MoistureGuard:	**60**
SilentGuard:	**61**

PRODUCT SPEC SHEET

Colors	Quarter Round	Reducer	T-Molding	Baby Threshold	Stairnosing	Wood Filler
Natural	HQRTA-05068	HREDC-05068	HTMDA-05068	HENDD-05068	HFSTC-05068	WF-626
Carmelized	HQRTA-05069	HREDC-05069	HTMDA-05069	HENDD-05069	HFSTC-05069	WF-693

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

PRODUCT SPEC SHEET