


Type \_\_\_\_\_  
 -01  
 P8643

Catalog No.	Lamping	Dimensions (Inches)	
		A	B
P8643-01	10 - 42w (4-pin), Quad, Triple, 2D and Twins	9-1/2	2-3/8 Case Height = 1-1/2"



**Specifications:**

General

- Will cold start and operate all specified lamps
- Long-life, 3.6 volt high-temperature Ni-Cad battery
- Test switch and charge light included in an easy-to-install switch box
- 5-year warranty
- 90-minute emergency operation
- Battery is recyclable through RBRC - call 1-800 8BATTERY
- Can be used with any compact fluorescent fixture utilizing compatible lamps
- Includes switch enclosure box and cover plate

Construction

- Painted steel case
- All leads enclosed in flex conduit

Lamps

- 10 - 42w 4-pin Rapid Start Compact lamps, incl.: twin tube, triple tube, quad, 2D & straight
- Initial lumen output is 650 for one lamp

Mounting

- For remote mounting only
- Maximum mounting distance is 50 feet or 1/2 AC ballast manufacturer's recommended maximum mounting distance, whichever is less

Electrical

- Dual voltage 120/277V, 60 Hz
- Meets or exceeds all NEC and NFPA Life Safety Code Emergency Lighting Requirements

Labeling

- UL listed

Progress Lighting  
 Post Office Box 5704  
 Spartanburg, South Carolina  
 29304-5704