Incandescent

Illluma-Flex[®] Mini Pendant Metal Shade Low Voltage

-09

Track



Halogen

P6138 🗌

Туре

Catalog No.	Finish Brushed NIckel	Dimensions (Inches)			
		Lamping	Α	В	С
P6138	-09	12v T4 35w (Incl)	2-5/8	9	72
B					

P6138

Specifications:

General

- Flex track mini-pendant
- Brushed nickel metal perforated shade
- Brushed nickel plated finish
- One 35w T4 lamp included
- Mounts anywhere along Illuma-Flex track sections, or on monopoints
- Includes adapter that allows unit to be mounted to P8516 transformer for Alpha track system also.

Mini Pendant Support

- A small wiring compartment is located just below the fitter to allow adjustment of cord length
- Cord is Teflon coated copper wire with a silicon sleeve that matches the brushed nickel finish

Electrical

- Attachment to 12 volt Illuma-Flex track with supplied track fitter, 120V Alpha-Track using supplied P8777 adaptor and P8516 Alpha-Track transformer or monopoint canopy (requires P8780 or P8794 accessory)
- Lamp has a GY6.35 bi-pin base

Labeling

• CSA-CSA/US listed

Progress Lighting Post Office Box 6701 Greenville, South Carolina 29606