

The new degree of comfort.™

Marathon[®] non-metallic electric water heaters are durable, lightweight, and warranted not to leak as long as you own your home*

Non-metalic Tank Features

- Seamless, blow-molded, polybutene tank impervious to rust and corrosion
- Multiple layers of filament wound fiberglass give the tank unmatched strength
- Polyurethane insulation helps reduce energy consumption
- Recessed drain valve is out of the way brooms and scrubbers
- High temperature polysulfone dip tube
- Tough molded polyethylene outer shell resists dents, scratches, and salt air

Efficiency

- .90 .94 EF
- Well insulated for reduced standby heat loss
- Pipe wrap energy saving kit included to achieve maximum energy savings

Performance

- FHR: 52-104 gallons, based on gallon capacity
- Recovery rate: 20 gallons GPH at a 90 degree rise

Capacity & Dimensions

• 30, 40, 50, 75, 85, 105-Gallon tall models and a 50 gallon short

Easy Installation & Service

 Marathon's lightweight tank is easier to maneuver and position. Bowl shaped tank bottom drains completely.

Plus...

- Thermally fused upper element provides protection against dry-firing – titanium lower element for superior resistance to lime build-up
- Full-flow, brass drain valve
- Temperature and pressure relief valve
- Standard replacement parts

Warranty

• Lifetime limited warranty on tank and 6 years on parts*

*See Residential Warranty Certificate for complete information

Units meet or exceed ANSI requirements and have been tested according to D.O.E. procedures. Units meet or exceed the energy efficiency requirements of NAECA, ASHIRAE standard 90, ICC Code and all state energy efficiency performance criteria.



Rheem Marathon

30 - 105-Gallon Capacities 240 Volt AC/Single Phase Electric



		DESCRIPTION	FEATURES		ROUGHING IN DIMENSIONS (SHOWN IN INCHES)				ENERGY INFORMATION	
T Y E	GAL. CAP.	MODEL NUMBER*	FIRST HOUR RATING G.P.H.	RECOVERY IN G.P.H. @ 90° RISE	TANK HEIGHT A	HEIGHT TO WATER CONN. B	DIAMETER C	APPROX. SHIP WT. (LBS.)	ENERGY FACTOR	AVERAGE ANNUAL OPER. COST
T A L L	30	MR30245	42	20	49	53	21-5/8	75	0.94	\$497
	40	MR40245 [†]	52	20	61-1/2	65-1/2	21-3/4	90	0.94	\$497
	50	MR50245 [†]	61	20	62-3/4	66-3/4	23-1/2	100	0.94	\$497
	75	MR75245†	78	20	58-5/8	62-5/8	28-1/4	122	0.92	\$508
	85	MR85245 [†]	91	20	66-1/4	70-1/4	28-1/4	134	0.92	\$508
	105	MR105245 [†]	104	20	66-3/4	70-3/4	30-1/4	152	0.91	\$514
SHORT	50	MSR50245	54	20	43-1/4	47-1/4	28-1/4	95	0.90	\$520

*Canadian models have different model numbers than U.S. models. Add a "C" before the model number (e.g., CMR85245) when ordering. Water heaters furnished with standard 240 volt AC, single phase non-simultaneous wiring, and 4500 watt upper and lower heating elements. 3000 and 3800 watt elements available. If heating elements of different wattages than those shown are demanded, they must be specifically requested.For height to top of T&P and heat traps add 3-1/2" to the height to water connection.Maximum test pressure: 300 PSI. Maximum working pressure: 150 PSI. Energy Factor and Average Annual Operating Costs based on D.O.E. (Department of Energy) test procedures. D.O.E. national average fuel rate electricity 10.65c/KWH.

ച

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating • 101 Bell Road Montgomery, Alabama 36117-4305 • www.rheem.com Rheem Canada Ltd./Ltée • 125 Edgeware Road, Unit 1 Brampton, Ontario L6Y 0P5 • www.rheem.com

3/4'

 \bigcirc