Sea Gull Lighting®

Life Illuminated | Since 1919

Job Name:

Job Type:

Comments:

Quantity:

96120S-32: Lx LED Clear Festoon Lamp - 3000K 24v

Dimensions:

Bulb Appearance:

Gas Filled:

Bulb Type: LED

Bulb Base: festoon

Volts: 24

Watts: 0.6

Watts Consumed: 0.648

Watts Rated: 0.6

Hours Rated: 35000

Bulb Temp: 3000 °K

CRI: 85

Features:

- LED's energy savings and long life helps protect the environment by using less energy and keeping numerous other types of lamps, with shorter life, out of land-fills

It's a snap to upgrade existing xenon linear systems to energy saving, money saving lighting.
No need to replace or re-invest in your entire system.
The LED festoon is an opportunity to retrofit or replace traditional under-the-counter systems and fills the need to provide "green" lighting solutions.

Applications: Task & accent lighting for undercabinet, coves, toe-kick spaces and so much more. Directional nature of LED is ideal for in-cabinet lighting.

Retrofit/Remodel Installations for Magnetic Transformer Systems - JUST REPLACE THE LAMP!
Compatible as a retrofit for existing Lx xenon lamp and compatible xenon lamp systems.
Note: The unique design of the PCB (Printed Circuit Board) makes over voltage due to under capacity a non-issue.

Retrofit/Remodel Installations for Electronic Transformer Systems 60w zero-load LED driver available for replacing electronic transformers due to minimum load requirement. Available drivers: 96223S-12 & 96223S-15.

Product Features: Ease of installation. Ease of retrofit/remodel. Bendable/flexibility of the system.

Dimmability: Dimmable with standard incandescent dimming switch.

A "Fit & Forget" Solution: Offering 35,000 hours of useful life (equivalent to 30 years at 20 hours of use per week)

Efficacy Warm White: 44 Lumens/Watt

Color Rendering: 3000K - CRI 90+

Material List:

Safety Listing:

ETL Listed for Damp Locations
cETL Listed for Damp Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (HC-1715FS)

LED Festoon Product Line Options & Features:
12v and 24v
Warm (3000K)
Cool (4000K)
Clear lens for optimal performance
Frosted lens to reduce glare
Color-coded PCB to visually distinguish between warm and cool color
temperature LED festoons
Color-coded end-caps to identify 12v (white) and 24v (black)
3 Year Warranty

UPC #:785652028083

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship
Individual	96120S-32	1	785652028083	2.25	2	0.5	0.001	0.1	Yes
Master Pack		10	10785652028080	9.18	2.5	1.25	0.017	0.2	Yes
NJ Pallet		25000		48	40	67.5	75	640	No
NV Pallet		25000		48	40	67.5	75	640	No