

## ANYSTREAM® Eco

### Low Flow Showerheads

#### GENERAL SPECIFICATION

Full-body, infinitely adjustable spray streams. Anystream plunger nozzle system delivers great spray intensity at any water pressure. Large operating handle for precise control and easy spray selection. Meets ANSI A112.18.1. 1/2" NPT inlet. Recommended for U.S. Green Building Council LEED Rating System Project Certification.

#### □ S-2253-E15

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.5 gpm/5.6 lpm

#### □ S-2253-E175

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.75 gpm/6.6 lpm

#### □ S-2253-E20

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

#### □ S-2252-E20

6-jet showerhead. 48 sprays. 2-3/4" face diameter. Solid brass large-body construction. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm

#### □ S-2005-H-E2

5-jet showerhead. 50 sprays. 3-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

#### □ S-2005-HB-E2

5-jet showerhead. 50 sprays. 4-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

**S-2253-E15**  
**S-2253-E175**  
**S-2253-E20**

**S-2252-E20**

**S-2005-H-E2**

**S-2005-HB-E2**

This space for Architect/Engineer approval.

