

SENTINEL MARK II®

SM-4030



Anti-Scald Balanced Pressure Shower & Bath

GENERAL SPECIFICATION

Sentinel Mark II concealed anti-scald balanced pressure shower and bath. Decorative etched metal index. Chrome plated brass wall plate. Chrome plated brass lever handle. Independent center sleeve allows up to 1" of rough-in variations. Adjustable temperature limit stop. Brass body. Pressure balancing & ceramic temperature regulating cartridge with built-in check valves. Can be installed back-to-back. Roughing-in template. Four port valve with 1/2" female copper sweat inlets and shower outlet (tub outlet 1/2 NPT female). S-2270-AF showerhead with flow control device that reduces flow to 2.5 gpm/9.46 lpm maximum to meet existing ASME A.112.18.1/CSA B125.1 standard. S-2500 shower arm and wall flange. S-1556 diverter tub spout. Meets ASSE 1016 & ASME 112.18.1/CSA B125.1 standards.

SM-4030

Anti-scald shower and bath with decorative index.

SM-4031

Anti-scald shower and bath with decorative index and Revere handle.

SM-4031



OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> IS	Integral stops
<input type="checkbox"/> LH	Less showerhead
<input type="checkbox"/> 1	S-2251-AF showerhead
<input type="checkbox"/> 2	S-2252-AF showerhead
<input type="checkbox"/> 2VR	S-2252-AF vandal-resistant showerhead
<input type="checkbox"/> 3	S-2253-AF showerhead
<input type="checkbox"/> 4	S-2220-AF showerhead
<input type="checkbox"/> 6	S-2288-AF showerhead
<input type="checkbox"/> 7	S-2291-AF showerhead
<input type="checkbox"/> 9	S-2292-AF showerhead

Contractor packs available upon request.

This space for Architect/Engineer approval.



