STERLING.


Features


- Compression molded from our exclusive solid Vikrell_® material
- Above-floor-drain (AFD) rough-in
- Durable high-gloss finish
- Modular 4-piece design
- Pivot "snap together" installation
- Wall surround available with smooth finish or glazed tile appearance
- 10-year consumer/3-year commercial limited warranty
- Caulkless seam installation
- 17-1/4" (43.8 cm) bath depth (floor to top of threshold)
- 60-1/4" (153 cm) x 31-1/4" (79.4 cm) x 75-1/2" (191.8 cm) complete unit rough-in dimensions include flanges
- 60" (152.4 cm) x 30" (76.2 cm) x 74-1/4" (188.6 cm) complete unit finished dimensions

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z124.1.2
- ASTM E162
- ASTM E662
- CSA B45.5





60" (152.4 cm) AFD BATH AND WALL

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Colors	Colors/Finishes	
71140112	60" (152.4 cm) AFD bath and wall surround, tile wall, left drain	0 🗆	Other	
71140122	60" (152.4 cm) AFD bath and wall surround, tile wall, right drain	0 🗆	Other	
71240112	60" (152.4 cm) AFD bath and wall surround, smooth wall, left drain	0 🗆	Other	
71240122	60" (152.4 cm) AFD bath and wall surround, smooth wall, right drain	0 🗆	□ Other	
Model	ADA Adaptive Component Description	Colors/	Finishes	
Model 71140118	ADA Adaptive Component Description AFD complete unit with age in place backers, left drain	Colors/	Finishes	
71140118	AFD complete unit with age in place backers, left drain	0	Other	

ACCORD®

Technical Information

Fixture*:						
Basin area:						
Bathing wel	I	46-1/4" (117.5 cm) x 20-1/2" (52.1 cm)				
Top area		52-1/4" (132.7 cm) x 22-1/2" (57.2 cm)				
To overflow:						
Water depth		11″ (27.9 cm)				
Capacity		34 gal (128.7 L)				
* Approximate measurements for comparison only.						
Model	door maximum width		door maximum height			
71140112 56- 71140122 71240112 71240122		3/4″ (144.1 cm)	56-1/2" (143.5 cm)			

Installation Notes

Install this product according to the installation guide.

Size the drain hole clearance to fit the drain assembly that will be used.

Studs should be positioned roughly as shown.

Bath cannot be installed without the wall surround.

The width of the module gets 5/8'' (1.6 cm) narrower at the back. Furring strips (approximately 1/4'' (6 mm)) should be used at the back corner studs if drywall will overlap the nailing flange.

