

# INSTALLATION INSTRUCTIONS

For Model 8219-PL

READ AND SAVE THESE INSTRUCTIONS

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**

## MOUNTING THE BACKPLATE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker and remove the old fixture from the ceiling, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Attach the circular strap (A) to the outlet box with mounting screws (C). The side of the circular strap (A) marked "GND" must face out.
4. Thread the two studs (B) into the circular strap (A) (You can adjust the length of the screws if necessary).

## CONNECTING THE WIRES (Fig. 2)

5. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap using the green screw provided. Tuck the wire connections neatly into the junction box. **MIN 90 DEGREE SUPPLY CONDUCTORS.**

## MOUNTING FIXTURE (Fig.1)

6. Align canopy (E) to studs (B) and secure with knurled knobs (D).
7. Install 1\*26W PL light bulb (G) (included) into socket (F) in accordance with the lamp's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE RATING)**
8. The ballast and lamp are combined, to replace or install, twist pins into socket as shown in Fig.3.
9. Align the holes in shade (G), to the screws (F) in canopy (E) and secure tightly with knurled knobs (H).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

