



Quality Generators Since 1927

25PTOC-3



Generator End:

- 100% copper windings - longer life and improved motor starting
- Single phase, 2 pole
- Rotating armature brush type
- Maintenance free bearings
- Class H Insulation
- Inherently regulated

Features:

- 4-wire Anderson full power plug included
- Large 3" voltmeter
- Cast iron gear case with 540 RPM 1 1/8" keyed input shaft
- Compact for easy storage
- Square D circuit breakers
- Protective PTO shield
- Rodent protection
- Helical gears for smooth operation
- Ground lug
- Lifting eye

Accessories (optional):

- PTO drive shaft (tumbling bar)
- Splined adapter
- Off road PTO trailer kit
- Manual transfer switches
- 3 point hitch kit with PTO shaft (requires splined adapter)
- 1000 RPM gearcase (requires splined adapter)

POWER RATING (watts)	25,000
AMPS (1)	104
VOLTS	120/240
PHASE	Single
VOLTAGE REGULATION	+/- 5%
RATING	125° C
TYPE	2 POLE REVOLVING ARMATURE
GENERATOR SPEED	3600 RPM
VOLTAGE CONTROL	INHERENTLY REGULATED
PTO INPUT SPEED	540 ⁽²⁾
REQUIRED INPUT HP (3)	50
MOTOR STARTING (Code G)	10 HP
120 VOLT RECEPTACLES	1x NEMA 5-20R
120/240 VOLT RECEPTACLES	1x NEMA 6-50R
DIMENSIONS (LxWxH)	29" x 16" x 20"
NET WEIGHT	320 lbs
SHIP WEIGHT	330 lbs
WARRANTY	3 YR

NOTES: (1) Unity (1.0) power factor (2) 1000 RPM factory installed gear case optional. (3) Recommended HP at PTO of tractor for full rated output. Each 2 HP provided at the PTO will result in 1kW electrical output up to the nameplate reading.



Presented by:

Toll Free: 1-800-733-2112
sales@wincogen.com

www.wincogen.com

225 South Cordova Avenue
Le Center MN, 56057