	ABT-115V-1786
Titaliio.	
Description:	Ultra Low Temperature Freezer 17 Cu.Ft. Capacity One solid swing exterior door, right hinged, not reversible Five insulated inner doors Microprocessor controller specifications Touch pad keys and four line display for easy programming Large LED temperature readout Audible and visual alarms with silence key for audible alarms Programmable high and low temperature alarm set points Programmable access code to limit access to set points and controller configuration Automatic voltage boost to compensate for low line voltages Normally open, normally closed alarm contacts and 4-20mA signal available to connect to central alarm system RS-232 serial output Battery backup on electronics during power outages Temperature range: -50°C to -86°C Four stainless steel shelves, adjustable on ½" centers Cam action handle for one hand latching of exterior door. Handle supplied with key lock and door switch for audible and visual alarms Four heavy duty swivel casters with locks Vacuum relief port for quick access after door closures CFC-free refrigerant Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 37.6"W x 36.3"D x 79.6"H Interior dimensions: 23.4"W x 23"D x 50"H 2" box capacity: 320 ea. Upright freezer rack capacity: 20 ea. UF442 racks 115V, 60Hz, 16 amp, HP: ½ x ½ UL/C-UL Listed NEMA plug configuration: NEMA 5-20
	Cascade refrigeration system Shipping weight: 700 lbs.
	- cppgc.g.m coc.