

Product Name:	ABT-HC-26C-TS
Description:	<p>TempLog Premier Glass Door Chromatography Refrigerator 26 Cu. Ft. capacity One swing glass door, self-closing (energy efficient, double pane vacuum insulated), right hinged, not reversible Microprocessor temperature controller: Adjustable operating temperature range: 1°C – 10°C Touch Screen Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms Password-protected Control Panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active Temperature Scale Bar Display Resettable 1-point Min/Max History Digital 24-hour Temperature Chart Temperature data logging USB Port for Data Transfer and Software Updates Real-time Operational Display Clock 4-20mA Output Electronic Troubleshooting Guide Electronic QR Code to Access Owner's Manual & Technical Support Contact Information Adjustable Alarm Volume Audible and Visual High/Low Temperature Alarms Sensor Error Alarm Power Failure Alarm Door Ajar Alarm Low Battery Alarm Operation Indicator Alarm Validation (audible, visual, and remote alarm) Alarm Mute with Ring Back Remote Alarm Contacts Four adjustable shelves (adjustable in ½" increments) Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Recessed door handle LED interior lights are safety shielded and switch controlled Swivel casters (adds 4" to height) One GFCI protected duplex electrical outlet Two 2" access ports with spring loaded self-closing, gasketed metal covers Probe access port (3/8") White laminated vinyl exterior White aluminum liner and stainless steel floor interior HFC-free refrigerant (R290), foam insulation and packaging Three year parts and labor warranty, plus an additional two year compressor parts warranty Exterior dimensions: 31 1/2" W* x 31" D x 82 5/8" H with casters; 78 5/8" H without casters. *Width w/access ports closed; 39 1/2" width w/access ports open Cycle defrost 115V, 60 Hz, 5.4 Amps, 1/3 HP, BTU/HR 4932 UL/C-UL listed ENERGY STAR CERTIFIED</p>

	Shipping weight: 345 lbs.
	Note: This unit requires two (2) outlets